Form (Feb.	



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Offic	. Senta Fe	
Lease No.	000127	 -
: Imie	Merfano	Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDEZ NOTICE OF INTENTION TO SHOOT OR ACIDEZ NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO BROADON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Well No. 100 is located 1650 ft. from Significant transforment (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Well No. 100 is located 1650 ft. from Significant transforment (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Well No. 100 is located 1650 ft. from Significant transforment (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) December 9 , 19 5 Well No. 100 is located 1650 ft. from Significant transforment (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) December 9 , 19 5 Well No. 100 is located 1650 ft. from Significant transforment (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ALL PRICE OF REPORT OF RE-DRILLING OR REPAIR (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ALL PRICE OF REPORT OF RE-DRILLING OR REPAIR (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ALL PRICE OF REPORT OF RE-DRILLING OR REPAIR (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ALL PRICE OF REPORT				0			
NOTICE OF INTENTION TO TEST WATER SHUT-OFF. NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO BOADDON WELL. SUBSECUENT REPORT OF RE-DRILLING OR REPAIR SUBSECUENT REPORT OF RE-DRILLING SUBSCUENT REPORT OF RE-DRILLING SUBSCUENT REPORT OF RE-DRILLING SUBSCUENT REPORT OF RE-DRILLING SUBSCUENT REPORT OF RE-DRILLING	NOTICE OF	INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF			
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE. SUBSCUENT REPORT OF RE-DRILLING OR REPAIR NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) NOTICE OF INTENTION TO ABANDON WELL NOTICE OF INT	NOTICE OF	INTENTION TO CHANGE PLA	NS	SUBSEQUENT REPORT OF ALTERING CASING			
NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO ABANDON WELL. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY MEXICO (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF	NOTICE OF	INTENTION TO TEST WATER	SHUT-OFF				
NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Company	NOTICE OF	INTENTION TO RE-DRILL OF	R REPAIR WELL				
Well No. 100 is located 1650 ft. from. Since and 1650 ft. from Willing of sec. 22 Well No. 100 is located 1650 ft. from. Since and 1650 ft. from Willing of sec. 22 Well No. 100 is located 1650 ft. from. Since and 1650 ft. from Willing of sec. 22 Well No. 100 is located 1650 ft. from. Since and 1650 ft. from Willing of sec. 22 Well No. 100 is located 1650 ft. from. Since and 1650 ft. from Willing of sec. 22 Well No. 100 is located 1650 ft. from. Since and 1650 ft. from Willing of sec. 22 Well No. 100 is located 1650 ft. from. Since and 1650 ft. ft. from Willing of sec. 22 Well No. 100 is located 1650 ft. from. Since and 1650 ft.	NOTICE OF	INTENTION TO SHOOT OR A	CIDIZE	SUBSEQUENT	REPORT OF ABANDONMEN	T	
Well No. 100 is located 1650 ft. from Sine and 1650 ft. from White of sec. 22 Sw. Sec. 22 Sol. Sw. H.M.P.M. (K Sec and Sec. No.) (Twp.) (Rance) (Meridian) Pallard P.C. St. Sen. Anne. (Point) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 5322 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) Prentured Pictured Cliffs perforated intervals 1978-1988; 1996-2008 (2 SFP) with \$1,760 gallons water and \$10,000 sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.P. 3100 ps.; max. pr. 3100 ps.; avg., if. pr. 1800-2000 psi. Injected one set of 20 balls. Company Address Soc. 397 Paraingson, Saw Mexico By Paraingson, Saw Mexico	NOTICE OF	INTENTION TO PULL OR ALT	TER CASING	SUPPLEMENTA	RY WELL HISTORY		
Well No. 100 is located 1650 ft. from Sine and 1650 ft. from Willing of sec. 22 SM Sec. 22 Soft M. M. P.M. (K sec. and sec. No.) (County or Subdivision) The elevation of the derrick floor above sea level is 6302 ft. (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) December 5, 1958. Total Depth 2088'. C.O.T.D. 2074'. Practured Pictured Cliffs perforested intervals 1978-1988; 1996-2008 (2 SFF) with \$1,780 gallons water and \$0,000\$ sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.P. 3100 psi, max. pr. 3100 psi, avg., tr. pr. 1800-2000 psi. Injected one set of 20 balls. I understand that this plan of work must receive approval in writing by the Geological Survey before operation may be conjumited. Company Address Original Signed R. G. Miller By	NOTICE OF	INTENTION TO ABANDON WI	ELL				
Well No. 100 is located 1650 ft. from Sine and 1650 ft. from Willine of sec. 22 SM Sec. 22 SM Sec. 22 SM H.M.F.M. (4 Sec. and Sec. No.) (Twp.) (Rome) (Meridian) Ballard P.C. Ext. Sen Jun. (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 5332 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) December 5, 1958. Total Depth 2088'. C.O.T.D. 2074'. Practured Pictured Cliffs perforested intervals 1978-1988; 1996-2008 (2 SFF) with \$1,750 gallons water and \$0,000 sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.F. 3100 psi, avg., tr. pr. 1800-2000 psi. Injected one set of 20 balls. Company Address Original Signed R. G. Miller Paradington, New Maxico By Terrollars Engineers				Band-Ne	THE CLOSE COMMIT	<u> </u>	
Well No. 100 is located 1650 ft. from Siline and 1650 ft. from Willine of sec. 22 SM Sec. 22 26N SH N.M.P.M. (Kisse, and Sec. No.) (Twp.) (Range) (Meridian) Ballard P.C. Ext. (Country or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 6302 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) December 5, 1953. Total Depth 2088*. C.O.T.D. 2074*. Practured Pictured Cliffs perforated intervals 1978-1988; 1996-2008 (2 SFF) with \$1,700 gallons water and \$0,000 sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.P. 3100 psi, max. pr. 3100 psi, avg., tr. pr. 1800-2000 psi. Injected one set of 20 balls. Company Address Original Signed R. G. Miller By		(INDICATE	ABOVE BY CHECK MARK N	NATURE OF REPORT	NOTICE, OR OTHER DATA)	
Sec. 22 26N (Range) (Range) (Meridian) Bellard P.C. Ext. (Field) (County or Subdivision) The elevation of the derrick floor above sea level is 5382 (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) December 5, 1958. Total Depth 2088'. C.O.T.D. 2074'. Practured Pictured Cliffs perforated intervals 1978-1988; 1996-2008 (2 SFF) with \$1,760 gallons water and \$0,000 sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.P. 3100 psi, max. pr. 3100 psi, avg. tr. pr. 1800-2000 psi. Injected one set of 20 balls. Company Address Original Signed R. G. Miller Paraington, Now Mexico By					Decembe	cr. 9, 19 5 6	
Realised P.C. Ext. San Juan (County or Subdivision) The elevation of the derrick floor above sea level is 6392 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) December 5, 1953. Total Depth 2083. C.O.T.D. 2074. Prestured Pictured Cliffs perforated intervals 1976-1983; 1996-2008 (2 SFF) with \$1,780 gallons water and \$40,000\$ sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.P. 3100 psi, max. pr. 3100 psi, avg. tr. pr. 1800-2000 psi. Injected one set of 20 balls. Company Address Original Signed R. S. Miller Paratington, New Mexico	Well No.	100 is located	d 1650 ft. from	$\begin{cases} \mathbf{NO}. \\ \mathbf{S} \end{cases} $ line and	1650 ft. from	w line of sec.	
Ballard P.C. Set. (Field) (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 6392. ft. DETAILS OF WORK (State names of and expected depths to objective ands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) December 5, 1958. Total Depth 2088'. C.O.T.D. 2074'. Practured Pictured Cliffs perforated intervals 1978-1988; 1996-2008 (2 SFF) with \$1,780 gallons water and \$0,000 sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.P. 3100 pei, max. pr. 3100 pei, avg. tr. pr. 1800-2000 pei. Injected one set of 20 balls. Company Address Paratingson, Sew Maxico Original Signed R. S. Miller By	SW S	Bec. 22	2 611	9 W	n.m.p.m.		
The elevation of the derrick floor above sea level is 6382 ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) December 5, 1958. Total Depth 2088'. C.O.T.D. 2074'. Practured Pictured Cliffs perforated intervals 1978-1988; 1996-2008 (2 SFF) with \$1,760 gallons water and \$0,000 sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.P. 3100 psi, max. pr. 3100 psi, avg. tr. pr. 1800-2000 psi. Injected one set of 20 balls. Company Address Farmingson, New Mexico Original Signed R. G. MILLER Permingson, New Mexico	(¼ S	ec. and Sec. No.)	(Twp.) (1	Range)	(Meridian)		
The elevation of the derrick floor above sea level is 6382 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) December 5, 1958. Total Depth 2081. C.O.T.D. 2074. Practured Pictured Cliffs perforated intervals 1978-1988; 1996-2008 (2 SFF) with \$1,780 gallons water and \$0,000 sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.F. 3100 psi, max. pr. 3100 psi, syg., tr. pr. 1800-2000 psi. Injected one set of 20 balls. Company Address Original Signed R. G. MILLER Farmington, New Mexico Details of Company Original Signed R. G. MILLER Parallegem, New Mexico	Ballard	P.C. Ext.	Contract of the contract of th				
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) December 5, 1958. Total Depth 2088'. C.O.T.D. 2074'. Practured Pictured Cliffs perforested intervals 1978-1988; 1996-2008 (2 SFF) with 41,780 gallons water and 40,000 sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.P. 3100 psi, max. pr. 3100 psi, avg. tr. pr. 1800-2000 psi. Injected one set of 20 balls. Company Address Original Signed R. G. Miller By Detailed the Presistance.		(Field)	(County or	Subdivision)	(State	e or Territory)	
December 5, 1958. Total Depth 2088'. C.O.T.D. 2074'. Freatured Pictured Cliffs perforated intervals 1976-1988; 1996-2008 (2 SFF) with 41,780 gallons water and 40,000 sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.P. 3100 psi, max. pr. 3100 psi, eyg. tr. pr. 1800-2000 psi. Injected one set of 20 balls. Company Address Original Signed R. G. Miller By	(Shaka anaman)	of and expected depths to o				indicate mudding jobs, cement-	
Practured Pictured Cliffs perforated intervals 1978-1988; 1996-2008 (2 SFF) with 41,780 gallons water and 40,000 sand. Flushed with 2520 gallons water. Injection rate was 65 B.P.M. B.D.P. 3100 psi, max. pr. 3100 psi, avg. tr. pr. 1800-2000 psi. Injected one set of 20 balls. I understand that this plan of work must receive approval in writing by the Geological Eurvey before operations may be compared. Company Si Paso Natural Ges Company Address Box 997 Original Signed R. G. Miller By	(State names	of and expected depois to o	ing points, and all ot	her important pro	oosed work)		
Company Si Paso Natural Ges Company Address Original Signed R. G. MILLER Paraington, New Maxico By	Fractan with 4: Inject: 1800-20	red Pictured Cli 1,780 gallons wa ion rate was 65 000 psi. Inject	ffs perforeted ter and 40,000 B.P.M. B.D.P. red one set of	intervals sand. Fi 3100 psi, 20 balls.	1978-1988; 199 Lumbod with 250 max. pr. 3100	gallone water.	
Address Original Signed R. G. MILLER Paraington, Nov Mexico By	_	R? Pago Natur			ogical Eurvey before oper	ations may be commenced.	
Original Signed R. G. MILLER By		arin and all and a second			_		
Title Petroleum Angineer		Fermington, N	lew Mexico	E			
				T:	tle Petroleum	Minoer	