Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

PORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 078932

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation	
1. Type of Well	West Bisti Unit	
□ Oil □ Ges ☑ Other Water Injection Well* P&A	8. Well Name and No.	
2. Name of Operator	West Bisti Unit 116	
Dugan Production Corp.	9. API Well No.	
3. Address and Telephone No.	7 30-045-05748	
P.O. Box 420, Farmington, NM 87499 (505) 325-1821	10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	*Bisti Lower Gallup	
1980' FSL - 1980' FWL	11. County or Parish, State	
Sec. 21, T26N, R13W, NMPM	San Juan, NM	
CUECK ADDRODDIATE BOY'S TO INDICATE MATURE OF MOTICE DEPO	OT OR OTHER DATA	

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Change of Plans Abandonment New Construction Recompletion Subsequent Report Non-Routine Fracturing Water Shut-Off Casing Repair Final Abandonment Notice Conversion to Injection COM. DI Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) DIAN, B

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

- Set cast iron bridge plug @ 4943'.
- 2. Spot 21 cu. ft. class "B" cement on top. Gallup plug 4786' 4943.
- 3. Perforate 5½ casing @ 2192'. Spot 61 cu. ft. class "B" cement @ 2193'. Displace cement to 1942'. Mesa Verde plug 1942' 2192'.
- 4. Perforate 5½" casing @ 1460'. Spot 171 cu. ft. class "B" cement w/4% gel @ 1467'. Displace cement to 963'. Pictured Cliffs Fruitland plug 963' 1460'.
- 5. Perforate 5½" casing @ 297'. Est. circulation. Cement to surface with 155 cu. ft. class "B" cement with 4% gel (5½" casing and surface annulus full of cement). Ojo Alamo surface plug 0' 297'.

Job complete 5/19/95.

Signed Signed China Alexander (This specifier Federal or State office use)	Title	Operations Manager	Date	5/22/95
Approved by	Title		Date	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements

ICT MANAGER

or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side