



A 10x10 grid with an 'X' in the 3rd column and 5th row.



U. S. LAND OFFICE **Window Rock**
SERIAL NUMBER **14-20-603-774**
LEASE OR PERMIT TO PROSPECT **Navajo**
Hun-nop-pi

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Hun-nop-pl
RECEIVED
PRIOR
J. S. GERRARD
ARMINGTON

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

Company BENSON-MONTIN Address 1501 REPUBLIC BUILDING, OKLAHOMA CITY
 Lessor or Tract HUN-NOP-PI Field BALLARD State NEW MEXICO
 Well No. 1 Sec. 19 T. 26 N. R. 8 W. Meridian N.M.P.M. County SAN JUAN
 Location 1532 ft. [N.] of N. Line and 1452 ft. [E.] of W. Line of SEC. 19 Elevation 6209
 (Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Date May 28th, 1955 Title Field Superintendent

The summary on this page is for the condition of the well at above date.

Commenced drilling February 17th, 19 55 Finished drilling April 15th, 19 55

OIL OR GAS SANDS OR ZONES

(Denote as by Θ)

No. 1, from 1891 to 1978 (G) No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
 No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Out and pulled from	Perforated		Purpose
							From—	To—	
8-5/8"	24#	8	J-55	83'	Texas Pattern	-	-	-	Surface
5-1/2"	17#	8	CF-81	1835'	Texas Pattern	-	-	-	Production
5-1/2"	14#	8	J-55	1835'	Texas Pattern	-	-	-	Production

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8-5/8"	92'	75	Pump & Plug		
5-1/2"	1897'	100	Pump & Plug		

PLUGS AND ADAPTERS

Heaving plug—Material None Length Depth set
Adapters—Material None Size

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
4"	Tin	SNG	150 qts.	4-11-55	1907-73	1973

TOOLS USED

Rotary tools were used from 92 feet to 1909 feet, and from _____ feet to _____ feet
Cable tools were used from Surface feet to 92 feet, and from 1909 feet to 1978 feet

Ran Tubing

DATES

State Potential Test

April 17th, 1955

Put to producing ----- May 26th -----, 1955

The production for the first 24 hours was ----- barrels of fluid of which -----% was oil; -----% emulsion; -----% water; and -----% sediment. Gravity, °Bé. -----

If gas well, cu. ft. per 24 hours **1,527,000**

Gallons gasoline per 1,000 cu. ft. of gas -----

Rock pressure, lbs. per sq. in. -----619

EMPLOYEES

Benson-Montin-Greer....., Driller

_____, Driller

Drilling Corp. Driller

_____, Driller

FORMATION RECORD

FROM--	TO--	TOTAL FEET	FORMATION
Surface	1885	1885	Surface sand and shale, Ojo Alamo, Kirtland and Fruitland formations
1885	1891	6	Coal
1891	1978	87	Pictured Cliffs Sand

