Form C-122

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

| Pool Basis  | Dakota                                 | For                                   | mation         | Dakot          | te  |                  | _County                                     | San J               | uen   |  |
|---|--|---------------------------------------|----------------|----------------|---|------------------|---|---------------------|---|--|
| Initial X   |  |                                       |                |                |   |                  |   |                     |   |  |
| Company Southwest   |  |                                       |                |                |   |                  |   |                     |   |  |
|   |  |                                       |                |                |   |                  |   |                     |   |  |
| Unit <u>B</u> Sec. <u>24</u> Twp. <u>26 N</u> Rge. <u>11 W</u> Purchaser <u>E1 Pase Natural Gas Company</u> Casing <u>4 1/2wt</u> . <u>10.50 I.D. 4.690</u> Set at <u>6300</u> Perf. <u>6168</u> To <u>6271</u> |  |                                       |                |                |   |                  |   |                     |   |  |
| Tubing 2 3/8 Wt. 4.70 I.D. 1.995 Set at 6217 Perf. To 6217  |  |                                       |                |                |   |                  |   |                     |   |  |
| Gas Pay: From 6168 To 6271 L 6217 xG .67 -GL 4165.3 Bar. Press. 12.0  |  |                                       |                |                |   |                  |   |                     |   |  |
|   |  |                                       |                |                |   |                  |   |                     |   |  |
| Producing Thru: Casing Tubing X Type Well Single-Gas  Single-Bradenhead-G. G. or G.O. Dual  Date of Completion: 7/14/62 Packer Reservoir Temp.  |  |                                       |                |                |   |                  |   |                     |   |  |
| Date of Complet:  | ion: //I                               | 402                                   | Packe          | r              |   | keservo          | ir Temp                                     |                     |   |  |
|   |  |                                       |                | OBSERV         | ED DATA   |                  |   |                     |   |  |
| Tested Through (Choke) (Choke) (Choke) (Type Taps   |  |                                       |                |                |   |                  |   |                     |   |  |
| Flow Da   |  | ata                                   |                |                | Tubing  |                  | Casing D                                    |                     | Duration  |  |
| No. (Prover) (Line) Size  | (Choke)                                | Press.                                | Diff.          | Temp.          | Press.  | Temp.            | Press.                                      | тетр.               | of Flow   |  |
|   | Size                                   | psig                                  | h <sub>w</sub> |                |   |                  |   | °F.                 |   |  |
| SI<br>1.  | 3/4 <sup>n</sup>                       |                                       | 412            |                | 1919<br>412   |                  | 1911<br>904                                 |                     | 7 day<br>3 hr.  |  |
| 2.  | 3/4                                    |                                       | 744            |                |   |                  |   |                     |   |  |
| 3.<br>4.  | <br>                                   |                                       |                |                |   |                  |   |                     |   |  |
| 5.  |  |                                       |                |                |   |                  |   | <u>]</u>            |   |  |
|   |  |                                       |                | FLOW CAL       | CULATION  | S                |   |                     | D-1 - 6 Fil   |  |
| Coeffici  | Coefficient                            |                                       | Pressure Flow  |                | Temp. Gravity factor  |                  |   |                     | Rate of Flow<br>Q-MCFPD   |  |
| (24-Hou   | $\mathbf{r}$ ) $\sqrt{h_{\mathbf{w}}}$ | $\sqrt{h_{\mathbf{w}}p_{\mathbf{f}}}$ |                | 2              | t   | F <sub>g</sub> _ | Fpv   |                     | 0 15.025 psia   |  |
| 1. 12.3650  |  | 4                                     | 24             | .96            | 88  | 9463             | 1.035                                       |                     | 4,974   |  |
| 3.  |  |                                       |                |                |   |                  |   |                     |   |  |
| 4.  |  |                                       |                |                |   |                  |   |                     |   |  |
| 5.  |  |                                       |                | <u> </u>       |   |                  |   |                     |   |  |
|   |  |                                       | PF             | RESSURE C      | LTAIUSIAS   |                  |   |                     |   |  |
| Gas Liquid Hydro  | carbon Rati                            | io                                    |                | _cf/bbl.       | •   | Speci            | ific Gravi                                  | ty Separate         | arator Gas<br>wing Fluid  |  |
| Consider of Liquid Hydrocarbons deg. Dpec   |  |                                       |                |                |   |                  | 1923  | P2                  | 3697.9  |  |
| · C   |  |                                       |                |                | _   | Pw               |   | _Pi                 | 839.0   |  |
| P <sub>w</sub>  | 2                                      |                                       |                | , ,            | 2 12  | <b></b>          | P <sub>c</sub> -P <sub>w</sub> <sup>2</sup> |                     | al. P.  |  |
| No. Pt (psia)   | P <sub>t</sub> <sup>2</sup>            | F <sub>c</sub> Q                      | $(F_cQ)^2$     | ~   (I<br>  (] | $(c_{\mathbf{c}^{\mathbf{Q}}})^2$<br>$(c_{\mathbf{c}^{-\mathbf{s}}})$ | P <sub>w</sub> 2 | Pc-Pw                                       |                     | $\begin{array}{c c} \text{al.} & P_{\mathbf{W}} \\ P_{\mathbf{W}} & P_{\mathbf{C}} \end{array}$ |  |
| 1. (psia)   |  |                                       |                | `              |   | 839.0            | 2858.9                                      | 1                   | .476  |  |
| 2.<br>3.  |  |                                       |                |                | <del></del>   |                  |   | _                   |   |  |
| 4.  |  |                                       |                |                |   |                  |   |                     |   |  |
| 5.  |  |                                       |                |                |   |                  |   |                     |   |  |
| Absolute Potent   | tial:                                  | 6,028                                 |                | MCFPD          |   | .75              |   | Fil is              |   |  |
| COMPANYADDRESS  | South<br>207 Pe                        | etr. Clu                              | b Plaza        | n Company      | orten. Ne   | w Mexico         | - AFT                                       | HVF                 |   |  |
| AGENT and TITL  |  | L. Hof                                | fmen,          | Production     | n Engine  | 30               | KU  | TLIA                | -   |  |
| W1TNESSED   | H. Mc                                  | Apally                                |                |                | <u> </u>  |                  | N IA  | 31 6 1 <sup>9</sup> | 062   |  |
| COMPANY   | El Pe                                  | PO MATUI                              | at nes         | Company<br>RE  | MARKS   |                  | \   | CON.                | somy  |  |
|   |  |                                       |                |                |   |                  | Soir  | nist.               | 3 /   |  |

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 600 F.
- $P_c$ = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mathbf{w}}$  Differential meter pressure, inches water.
- $F_g = Gravity$  correction factor.
- $Ft_{-}$  Flowing temperature correction factor.
- $F_{DV}$  Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{\mathbf{W}}$  cannot be taken because of manner of completion or condition of well, then  $P_{\mathbf{W}}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\mathbf{t}}$ .