STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting pecker leakage tests in Southeast New Mexico

1986

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perator <u>COL</u>	UMBUS ENERGY	CORP	ORATION	Lease		CON HA	LE	Well No.	1
				Rge{	3	<u> </u>	Cour	sty SAN	JUAN
of Well: Unit B Sec. 24 Twp. 26				TYPE OF PROD. (Oil or Gas)		METHOD OF PROD. (Flow or Art. LH1)			PROD. MEDIUM (Tbg. or Ceg.)
Upper Completion PICTURED CLIFFS (TA)			GAS		FLOW			TBG	
Completion DAKOTA (NON-PRODUCTIVE)			GAS		FLOW			TBG	
				W SHUT-IN P			·	Stabilized?	Yes or No)
Upper NA Length of time shut-in			-m	Si press. palg 385			Yes		
Completion NA NA NA Hour, date shut-in Length of time shut-in		-in			· · · · · · ·	Stabilized? (Yes or No)			
Lower NA	·		NA		-	0-		Y	es
		·		FLOW TEST	NO. 1				
mmenced at (hour, da	9-26-86				Zone pro	oducing (Upp	er er Lower):	Lower	
TIME LAPSED TIME		PRESSURE			PROD. ZONE		REMARKS		
(hour, date)	SINCE*	Upper CSG	Completion	Lower Completion	TE	MP.			
0:00 a.m.		CSG	385	-0-		•	Lower	Zone	Opened
.0:15 a.m.	15 min		385	-0-			ıı		
0:30 a.m.	30 min		385	-0-	ļ		11	11	11
lO:45 a.m.	45 min		385	-0-			11	11	11
11:00 a.m.	60 min		385	-0-			- 11		н ,
									10
roduction rate o	luring test				• .				
Oil:BOPD based on			Bbls. i	Bbls. in Hours		G12v	GOR		
as:		-0-	MCF	PD; Tested thn	u (Orifice	or Meter	r):		<u> </u>
			MID-TI	est shut-in i				Ja	
Upper Completion Length of time shut-			ut-in	Si press. pr	ress. pelg			Stabilized? (Yes or No)	
Lower Completion Length of time shut-			ui-In	SI press. psig		Stabilized? (Yes or No)			
		L			··············	6	700		

REMARKS

$\pi \cap$	w	TROCT	BIO	-
FLU	w	TEST	NU.	4

Lower Completion

PRESSIBL

Lipper Completic

Zone producing (Upper or Lower):

PROD. ZONE

TEMP.

	·				
ion rate during test					
BOPD based on B	Bbls. in Hours Grav GOR _				
MCFPD: Tester	d thru (Orifice or Meter):				
	•				
y certify that the information herein contained is true:					
SEP 3 0 1986 ₁₉	Operator COLUMBUS ENERGY CORPORATION				
Mexico Oil Conservation Division	By Kay S. Cokster				
Original Signed by CHARLES GHOLSON	by May's result				
	Title PRÓDUCTION & DRILLING TECHNICIAN				
DEPUTY GIL & GAS INSPECTOR, DIST. #3	Date September 30, 1986				
, ,	September 30, 1986				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

mmenced at (hour, date)**

LAPSED TIME

SINCE **

TIME

our, dete)

At least 72 hours prior to the commencement of any packer leakage test, the operator . Il notify the Division in writing of the exact time the test is to be commenced. Offset regrators shall also be so notified.

- 5. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for some days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).