

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

RECEIVED
MAIL ROOM

OCT 19 1995 PM 2:18

SUBMIT IN TRIPLICATE

070 Farmington, NM

1. Type of Well

Oil Well Gas Well Other Injection Well*

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL - 1980' FEL
Sec. 19, T26N, R13W, NMPM

5. Lease Designation and Serial No.

NM 013492

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 107

9. API Well No.

30-045-05794

10. Field and Pool, or Exploratory Area

*Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

Notice of Intent

Subsequent Report

Final Abandonment Notice

TYPE OF ACTION

Abandonment

Recompletion

Plugging Back

Casing Repair

Altering Casing

Other

Change of Plans

New Construction

Non-Routine Fracturing

Water Shut-Off

Conversion to Injection

Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plan to plug as follows:

1. Set cast iron bridge plug 50' below Gallup top (5197'). Spot 50' Class B cement plug on top of bridge plug.
2. Perforate 50' below Mesa Verde top (3181'). Spot 100' Class B cement plug with required excess inside and outside casing.
3. Perforate 50' below Pictured Cliffs top (1685'). Spot Class B + 4% gel plug inside and outside casing to cover Fruitland top (1387').
4. Perforate 50' below Ojo Alamo top (327'). Pump Class B + 4% gel cement down 5 1/2" and circulate to bradenhead to cover Ojo Alamo and surface.

RECEIVED
OCT 30 1995
OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed John Alexander

Title Operations Manager

Date 10/17/95

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

APPROVED
AS AMENDED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD

DISTRICT MANAGER