

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL - 660' FEL
Sec. 18, T26N, R13W, NMPMFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 013492

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 103

9. API Well No.

30-045-05810

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Run tubing and tag up $\pm 4105'$.
2. Perforate Mesa Verde at 2440'.
3. Spot 77 cu. ft. Class B cement with 2% CaCl_2 at 2457. Displace cement to 2240'. Mesa Verde plug 2240' - 2457'.
4. Perforate Pictured Cliffs at 1830'.
5. Spot 176 cu. ft. Class B cement with 4% gel at 1843. Displace cement to 1491'. Pictured Cliffs Fruitland plug 1491' - 1843'.
6. Perforate below surface casing at 483'.
7. Run tubing to 498'. Pump cement to surface in 5 1/2" casing. Close casing valve. Pump cement to surface through bradenhead. Close valve. POH with tubing. NO BOP. Fill 5 1/2" casing with cement. Total cement on surface plug 164 cu. ft. Class B with 4% gel followed by 57 cu. ft. Class B cement. Surface plug 0' - 483'.

Job complete 6-8-93.

Approved as to plugging of the well here.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed John Alexander
(This space for Federal or State office use)Title Operations ManagerDate 6/9/93Approved by _____
Conditions of approval, if any:

Title _____

APPROVED

JUN 10 1993

DISTRICT MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.