

(SUBMIT IN TRIPPLICATE)
**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

Land Office **SF**
Lease No. **079679**
Unit **Delhi-Taylor**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PUMP OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Sandoil Frac.

RECEIVED
MAY 24 1961
U. S. GEOLOGICAL SURVEY
WASHINGTON, D. C.

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 18, 1961


Well No. **6** is located **1650** ft. from **N** line and **1650** ft. from **E** line of sec. **17**,
NE 1/4 SW 1/4 Section 17, **26N** **11W** **NMPM**,
(Township) (Range) (Meridian)
Basin Dakota **San Juan** **New Mexico**,
(County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6162** ft.

DETAILS OF WORK

(State names of and expected depths of objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

5-16-61 Total Depth 6190'. Clean Out Total Depth 6157'.
Sandoil fractured Dakota through perforated intervals 5990'-6015' with
32,760 gals. oil and 50,000# sand. Breakdown pressure--1700 psi;
maximum treating pressure--3800 psi; average treating pressure--3000
psi. Injection Rate: 38.5 Bbls./Min. Flush with 3360 gals. crude



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Products Company**
Address **Post Office Box 1560**
Farmington, New Mexico

By **ORIGINAL SIGNED BY: VAN E. DYKES**
Title **Petroleum Engineer**