

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved
Budget Item No. 42-R1423.
5. LEASE DESIGNATION AND SERIAL NO.

SF-079679

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR EL PASO PRODUCTS COMPANY	8. FARM OR LEASE NAME Delhi Taylor
3. ADDRESS OF OPERATOR Post Office Box 1560, Farmington, New Mexico 87401	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1792'/S, 1750'/W, Section 17, Township 26 North, Range 11 West	10. FIELD AND POOL, OR WILDCAT Gallegos Gallup
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6151' GR
	12. COUNTY DESIGNATION San Juan
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Started Operations 6-8-68
Finished Operations 6-12-68

1. Loaded hole with mud laden fluid.
2. Squeezed Gallup perforations 5250'-4970' 32 sx cement.
3. Shoot pipe loose at free point 2227' and pull.
4. Spot 30 sx cement plug, 4% gel, 2279' to 2134' in and out of stub.
5. Spot 30 sx cement plug, 4% gel, 1348' to 1238'. Across top of Picture Cliff.
6. Spot 30 sx cement plug, 4% gel, 475' to 365'. Base Ojo Alamo.
7. Place 10 sx. cement plug in top of surface casing with welded marker in place.
8. Clean location.

RECEIVED
JUL 3 1968U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

Original Signed By:

SIGNED Jim Payne

TITLE Agent

DATE July 3, 1968

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side