

NEW MEXICO OIL CONSERVATION COMMISSION
GAS WELL TEST DATA SHEET - - SAN JUAN BASIN

(TO BE USED FOR FRUITLAND, PICTURED CLIFFS, MESAVERDE, & ALL DAKOTA
EXCEPT BARKER DOME STORAGE AREA)

Pool Ballard Pictured Cliffs Formation Pictured Cliffs County San Juan
Purchasing Pipeline Southern Union Gas Company Date Test Filed 3/20/56
Operator Southern Union Gas Company Lease Newton Well No. 11
Unit B Sec. 17 Twp. 26-N Rge. 8-W Pay Zone: From 2012' To 2102'
Casing: OD 5-1/2" WT. 15.5# Set At 2012' Tubing: OD 1" WT. 1.7# T. Perf. _____
Produced Through: Casing XX Tubing _____ Gas Gravity: Measured _____ Estimated .660
Date of Flow Test: From 1/16/56 To 1/24/56 * Date S.I.P. Measured 11/9/55
Meter Run Size 4" Orifice Size 1-3/8" Type Chart Normal Type Taps Flange

OBSERVED DATA

Flowing casing pressure (Dwt) _____ psig + 12 = _____ psia (a)
Flowing tubing pressure (Dwt) _____ psig + 12 = _____ psia (b)
Flowing meter pressure (Dwt) _____ psig + 12 = _____ psia (c)
Flowing meter pressure (meter reading when Dwt. measurement taken):
Normal chart reading _____ psig + 12 = _____ psia (d)
Square root chart reading (_____) ² x spring constant _____ = _____ psia (d)
Meter error (c) - (d) or (d) - (c) _____ ± _____ = _____ psi (e)
Friction loss, Flowing column to meter:
(b) - (c) Flow through tubing: (a) - (c) Flow through casing _____ = _____ psi (f)
Seven day average static meter pressure (from meter chart):
Normal chart average reading 218 psig + 12 = 230 psia (g)
Square root chart average reading (_____) ² x sp. const. _____ = _____ psia (g)
Corrected seven day avge. meter press. (p_f) (g) + (e) _____ = 230 psia (h)
P_t = (h) + (f) _____ = 230 psia (i)
Wellhead casing shut-in pressure (Dwt) 669 psig + 12 = 681 psia (j)
Wellhead tubing shut-in pressure (Dwt) 669 psig + 12 = 681 psia (k)
P_c = (j) or (k) whichever well flowed through _____ = 681 psia (l)
Flowing Temp. (Meter Run) 60 °F + 460 _____ = 520 °Abs (m)
P_d = 1/2 P_c = 1/2 (l) _____ = 340 psia (n)

FLOW RATE CALCULATION

Q = 442 X $\left(\frac{\sqrt{(c)}}{\sqrt{(d)}} = \frac{\text{None}}{\text{None}} \right) = \text{None}$ MCF/da
(Integrated)

DELIVERABILITY CALCULATION

D = Q 442 $\left[\frac{(P_c^2 - P_d^2)}{(P_c^2 - P_w^2)} \right]^{0.85} \frac{.86870}{\text{None}} = \text{None}$ MCF/da.

SUMMARY

P_c = 681 psia
Q = 442 Mcf/day
P_w = 230 psia
P_d = 340 psia
D = 384 Mcf/day

Company Southern Union Gas Company
By L. S. Muennink L. S. Muennink
Title Jr. Petroleum Engineer
Witnessed by _____
Company _____

- * This is date of completion test.
- * Meter error correction factor

REMARKS OR FRICTION CALCULATIONS

GL	(1-e ^{-S})	(F _c Q) ²	(F _c Q) ² (1-e ^{-S}) R ²	P _t ² (Column i)	P _t ² + R ²	P _w
			Friction Loss Negligible			

OK



OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received	3	
DISTRIBUTION		
	1	
Register		
Books	1	
Collection Office		
Photo Land Office		
A. G. S.	1	
Transporter		
File	1	✓