

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF - 078897

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR EL PASO PRODUCTS COMPANY	8. FARM OR LEASE NAME Western
3. ADDRESS OF OPERATOR P. O. Box 1560, Farmington, New Mexico 87401	9. WELL NO. 4
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface  660'/N, 1983'/E, Section 18, Township 26 North, Range 11 West	10. FIELD AND POOL, OR WILDCAT Gallegos Gallup
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6083' GL
12. COUNTY OR PARISH San Juan	13. STATE New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Start Operations 7-1-68, Finish 7-3-68

1. Load hole with mud laden fluid.
2. Squeeze perforations, 25 sx cmt, 5151-4932'.
3. Shoot pipe loose at free point - 1490'.
4. Spot 30 sx cmt, 4% gel, 1542-1397' in and out of stub.
5. Spot 30 sx cmt, 4% gel, 1358-1248' - Top Pictured Cliffs.
6. Spot 30 sx cmt, 4% gel, 410-300' - Base Ojo Alamo.
7. Place 10 sx cmt top surface casing with welded marker in place.
8. Clean location.

RECEIVED

SEP 27 1968

U. S. GEOLOGICAL SURVEY



18. I hereby certify that the foregoing is true and correct

Original SIGNED by Jim Payer TITLE Agent DATE August 15, 1968

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side