

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT NAME
2. NAME OF OPERATOR X Dry hole - convert to water well.	8. FARM OR LEASE NAME
3. ADDRESS Pan American Petroleum Corporation	9. COUNTY OR PARISH
4. LOCATION OF WELL N. O. Bent 180, Farmington, New Mexico (See also space 17 below.) At surface 790 FSL and 790 FWL Section 8, T-26-N, R-18-W.	10. FIELD AND POOL, OR WILDCAT
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data	17. STATE

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and log form.)

17. DESCRIBE PROPOSED WORK. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Well Data:

Elev. RDB 5820 GL 5808 (GL to RDB 12.35')

Spudded May 1, 1963 - 11" hole.

Casings: 8 5/8" (24#, J-55) CSA 1527 / 350 SX regular 45 gel with 12 1/2" Tar Plug/SX and 50 SX neat. Circ 90 SX

40 SX Cement plug set 1480 - 1580

10 SX Cement plug from surface - 30'

(P&A June 11, 1963; TD 7148)

1. Rig up pulling unit, drill out surface cement plug and circulate casing clean to top of cement at about 1480.
2. Pull tubing and set cast iron bridge plug above top of cement (See lowest perforation below).
3. Perforate 1 SPF
935 - 955 (20')
1175 - 1185 (10')
1205 - 1220 (15')
1285 - 1295 (10')
55'

18. I hereby certify that the foregoing is true and correct.

SIGNED **Fred L. Nabers**

SIGNED BY

TITLE

District Engineer

DATE

June 10, 1964

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Verbally approved June 10, 1964 - John Ward to Frank H. Hollingsworth.

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.