Form	9 - 331	
(May	1963	

UNITED STATES UNITED STATES SUBMIT IN TRIPLICATES DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

_	 440,000,000,000,000	 0. 22 1	ودات والا
,,	DESIGNATION		
			_/

	SF-078899-A		
SUNDA (Do not use this form	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
METT Z MEDT Z	отнек	7. UNIT AGRESMENT NAME	
2. NAME OF OURRATOR	8. FARM OR LEADE NAME		
EL PASO PRODU	Western A		
3. ADDRESS OF OPERATOR	9. WELL NO.		
- Post Office Box I	. 1		
4. LOCATION OF WELL (Report See also space 17 below.) At surface	Gallegos Gallup 11. sec., T., Z., M., OR ELE, AND		
660'/S, 1980'/W	, Section 8, Township 26 North, Range 11 West	SURVEY OR AREA	
14. PERMIT NO. 15. REPUATIONS (Show whether DR DT CD etc.)		Sec. 8, T26N, R11W NMPM	
	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY EXCENSES 12. STATE	
	6168 GR	San Juan New Mexico	
16.	The de America De Tell De Atre Caller De		

appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	-	SUBSEQUENT BEPO	RT OF:
TEST WATER SHUT-OFF PULL OR ALTE FRACTURE TREAT MULTIPLE CO SHOOT OR ACIDIZE ABANDON* REPAIR WELL CHANGE PLAN (Other)	MPLETE	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (NOTE: Report results of multiple Completion or Recompletion Rep	BEPAIRING WELL ALTERING CLOING ABANDONMENT* X le completion on Weil out and Log form

Started Operations 5-30-68. Finished Operations 6-4-68.

- Load hole with mud laden fluid.
- 2. Squeeze Gallup perforations 5324' to 4930' 45 sx. cement.
- 3. Shoot pipe at free point 1513' and pull.
- 4. Spot 85 sx. cement plug 4% gel 1570' to 1287' in and out of stub and Picture Cliff.
- 5. Spot 40 sx. cement plug 4% gel 580' to 459' Base of Ojo Alamo.
- Spot 10 sx. cement plug in top surface casing with welded marker in place.
- Clean location.

RECEIVED

JUL

U. S. GEOLOGICAL SU WEY

Original Signed By: Jim Payne	TITLE	Agent		DATE _	July 3, 1968	-
(This space for Federal or State office use)						=
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE		. ·	DATE		_