

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on reverse side)Form Approved  
Budget Project No. 42-R1424  
5. LEASE REGISTRATION AND SERIAL NO.

SF-078899-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR EL PASO PRODUCTS COMPANY	8. FIRM OR LEASE NAME Western A
3. ADDRESS OF OPERATOR Post Office Box 1560, Farmington, New Mexico 87401	9. WELL NO. 3
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660'/S, 660'/E, Section 8, Township 26 North, Range 11 West.	10. FIELD AND POOL, OR WILDCAT Gallegos Gallup
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6229' GR
	11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Sec. 8, T26N, R11W NMPM
	12. COUNTY OR TERRITORY 13. STATE San Juan New Mexico

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Start Operations 5-27-68.

Finish Operations 5-29-68.

1. Load hole with mud laden fluid.
2. Squeeze Gallup perforations 5386' to 5255' - 15 sx. cement.
3. Shoot pipe at free point 2443' and pull.
4. Spot 30 sx. cement plug 4% gel 2495' to 2330' in and out of stub.
5. Spot 30 sx. cement plug 4% gel 1546' to 1436' Across top Picture Cliff.
6. Spot 30 sx. cement plug 4% gel 641' to 531' at base of Ojo Alamo.
7. Spot 10 sx. cement plug in top surface casing with welded marker in place.
8. Clean location.



RECEIVED

JUL 3 1968

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

Original Signed By:

SIGNED Jim Payne

TITLE Agent

DATE July 3, 1968

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side