
Form 9-331 a (Feb. 1951)



ILLEGIBLE

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4. Approval expires 12-31-60.

Land Office Santa Fe

Lease No. 384 G16089

Unit F. Engagers

NOTICE OF INTENTION TO DRILL.	SUBSEQUENT REPORT OF WATER SHUT OFF T 1 0 1052
OTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING 1330
OTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CHECKET STEET
TICE OF INTENTION TO RE-DRILL OR REPAIR WELL	
TICE OF INTENTION TO SHOOT OR ACIDIZE	
OTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
OTICE OF INTENTION TO ABANDON WELL	Report of Perforations Report of Sand/Oil Procing
(INDICATE ABOVE BY CHECK	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
(INDICATE ABOVE BY CHECK	
	Cetaber 9., 19
B. Samudana	
i. P. Sanaders II No. 3 is located 440ft.	from $\begin{bmatrix} \mathbf{S} \\ \mathbf{S} \end{bmatrix}$ line and \mathbf{S} t. from $\begin{bmatrix} \mathbf{E} \\ \mathbf{S} \end{bmatrix}$ line of sec.
11 110.	[5]
(½ Sec. and Sec. No.) (Twp.)	(Hange) (Meridiah)
(Field) (Co	ounty of Subulvision) (State or Territory)
ne elevation of the derrick floor above se	no loved to 44.94. ft
se elevation of the derrick NOOF above se	
	ETAILS OF WORK
DE	ETAILS OF WORK
DE tate names of and expected depths to objective sands; sh ing points, an	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cend all other important proposed work)
DE ate names of and expected depths to objective sands; shing points, an	ETAILS OF WORK
DE ate names of and expected depths to objective sands; shing points, an	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cend all other important proposed work)
DE ate names of and expected depths to objective sands; shing points, an arrivated 7° casing 55%4-5661	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, central other important proposed work) 5610-5615 v/l lane belle jet shots per fi
DE ate names of and expected depths to objective sands; shing points, an arrivated 7° casing 55%4-5661	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, central other important proposed work) 5610-5615 v/l lane belle jet shots per fi
DE ate names of and expected depths to objective sands; she ing points, an erforated 7" enging 5564-5601 & 72°, 88 shots. Paged Callup formation, down 7" /30,000# 20/40 sand & 30,240 gal	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, central other important proposed work) 1. 5616-5615 1. Lane Wells jet shote per file. 1. Lane oil ty Devell using 60 rubber free 1. 100 1. 100 1. 5606 1. 560
DE ate names of and expected depths to objective sands; she ing points, an erforated 7" enging 5564-5601 & 72°, 88 shots. Paged Callup formation, down 7" /30,000# 20/40 sand & 30,240 gal	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, central other important proposed work) 1. 5616-5615 1. Lane Wells jet shote per file. 1. Lane oil ty Devell using 60 rubber free 1. 100 1. 100 1. 5606 1. 560
DE ate names of and expected depths to objective sands; she ing points, an enforcted 7" ensing 5564-5601" & 72", 68 shets. Proced Gallup formation, down 7" /20,000* 20/40 sand & 30,240 gallup 2000* 2000* 20/40 gallup 2000* 2000* 2000* 20/40 sand & 30,240 gallup 2000* 2000	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, central other important proposed work) 5610-5615 v/l lane belle jet shots per fi
DE ate names of and expected depths to objective sands; sherforeted 7" ensing 5564-5601* & 72°, 68 sheets. Proced Gallup formation, down 7" /30,000# 20/40 sand & 30,240 gal	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, central other important proposed work) 1. 5616-5615 1. Lane Wells jet shote per file. 1. Lane oil ty Devell using 60 rubber free 1. 100 1. 100 1. 5606 1. 560
DE ate names of and expected depths to objective sands; she ing points, an erforated 7" enging 5564-5601 & 72°, 88 shots. Paged Callup formation, down 7" /30,000# 20/40 sand & 30,240 gal	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, central other important proposed work) 1. 5610-5615 w/l lame Wells jet shots par for the size of the size
DE ate names of and expected depths to objective sands; she ing points, an expected 7" enging 5564-5601 & 72°, 88 shots. Page Callup formation, down 7" /30,000# 20/40 sand & 30,240 gal	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, central other important proposed work) 1. 5616-5615 1. Lane Wells jet shote per file. 1. Lane oil ty Devell using 60 rubber free 1. 100 1. 100 1. 5606 1. 560
DE ste names of and expected depths to objective sands; sharpfore-ted 7" enging 55%4-5601 & 72°, 88 whots. The continue formation, down 7" (30,000 20/40 and a 30,240 ga) of 21,000, Nax. TP 2700°, Min. To the in 10 min. 600°. Inj. rate	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cond all other important proposed work) 1. 5610-5615' w/L lame Wells jet shote par fit cassing, thru 7' chaing perfs. 5550-5601' & ls. lse. oil by levell using 60 rubber frue P.E. 24005. Flushed w/260 Role. oil. Steam A3.5 BFN. Time of treatment 24 min.
DE ste names of and expected depths to objective sands; shing points, and referreted 7" enging 5584-5601 & 221, 88 sheets. Read Gallup formation, down 7" 30,000/ 20/40 sand & 30,240 gallup 2400/, Nax. TP 2700/, Min. Tr	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cond all other important proposed work) 1. 5610-5615' w/L lame Wells jet shote par fit cassing, thru 7' chaing perfs. 5550-5601' & ls. lse. oil by levell using 60 rubber frue P.E. 24005. Flushed w/260 Role. oil. Steam A3.5 BFN. Time of treatment 24 min.
te names of and expected depths to objective sands; shing points, an arrowal of casing 5564-5601. The same of and expected depths to objective sands; shing points, and arrowal of casing 5564-5601. The same of and expected depths to objective sands; shing points, and arrowal of casing 5564-5601. The same of and expected depths to objective sands; shing points, and arrowal of casing 5564-5601. The same of and expected depths to objective sands; shing points, and arrowal of casing 5564-5601. The same of and expected depths to objective sands; shing points, and arrowal of casing 5564-5601. The same of and expected depths to objective sands; shing points, and arrowal of casing 5564-5601. The same of and expected depths to objective sands; shing points, and arrowal of casing 5564-5601. The same of arrowal of casing	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cond all other important proposed work) 1. 5610-5615' w/L lame Wells jet shote par fit cassing, thru 7' chaing perfs. 5550-5601' & ls. lse. oil by levell using 60 rubber frue P.E. 24005. Flushed w/260 Role. oil. Steam A3.5 BFN. Time of treatment 24 min.
DE ste names of and expected depths to objective sands; she ing points, an expected 7" easing 55%4-5601. It is need Gallup formation, down 7" 30,000/ 20/10 sand & 30,240 gallup 21,000/, Max. TP 2700/, Min. To re in 10 sim. 800/. Inj. rete	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cond all other important proposed work) 1. 5610-5615' w/L lame Wells jet shote par fit cassing, thru 7' chaing perfs. 5550-5601' & ls. lse. oil by levell using 60 rubber frue P.E. 24005. Flushed w/260 Role. oil. Steam A3.5 BFN. Time of treatment 24 min.
te names of and expected depths to objective sands; shing points, and referred 7" enging 5584-5601. 4 22', 88 shots. 20,000' 20/40 sand & 30,240 gal 2400', Max. TP 2700', Min. Tree in 10 sin. 800'. Inj. rate 1 understand that this plan of work must receive apprompany	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cond all other important proposed work) 1. 5610-5615' w/L lame Wells jet shote par fit cassing, thru 7' chaing perfs. 5550-5601' & ls. lse. oil by levell using 60 rubber frue P.E. 24005. Flushed w/260 Role. oil. Steam A3.5 BFN. Time of treatment 24 min.
ate names of and expected depths to objective sands; she ing points, an ing points, and	ETAILS OF WORK now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cond all other important proposed work) 1. 5610-5615' w/L lame Wells jet shote par fit cassing, thru 7' chaing perfs. 5550-5601' & ls. lse. oil by levell using 60 rubber frue P.E. 24005. Flushed w/260 Role. oil. Steam A3.5 BFN. Time of treatment 24 min.