



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4
Approval expires 12-31-60.

Land Office New Mexico
Lease No. NM 03159
Unit O. H. Randal "B"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	☒
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

O. H. Randal "B"

Farmington, New Mexico January 7, 1959

Well No. 1 is located 790 ft. from S line and 1890 ft. from W line of sec. 10
SW/4 of Section 10 T-26-N R-11-W N. M. P. M.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wilcox San Juan New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6340 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

O. H. Randal "B" No. 1. On December 4, 1958, 7" casing was landed at 6447' with 325 sacks 6% gel cement with 2 pounds tuff plug per sack, followed by 75 sacks neat cement. Tested casing with 3000 pounds pressure for thirty minutes, which held with no drop in pressure. Top cement by temperature survey 4600'. Released rotary rig December 5, 1958.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 487
Farmington, New Mexico

ORIGINAL SIGNED BY
L. O. Speer, Jr.

By _____
 Title Field Superintendent