

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other P&A

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1190' FSL - 1450' FWL
Sec. 11, T26N, R9W, NMPM

FORM APPROVED

Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 012737

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Huerfanito 6

9. API Well No.

30-045-05910

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐
- Notice of Intent
-
- ☒
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☒
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☐
- Other _____
-
- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☐
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugged well as follows:

- Spot 18 cu. ft. Class B cement plug @ 6374'. Shut in overnight. Did not tag cement. Spot 30 cu. ft. class "B" with 3% CaCl₂ @ 6374'. Tag cement @ 6155'. Dakota plug 6155' - 6374'.
- Spot 18 cu. ft. Class B cement plug @ 5450'. Gallup plug 5245' - 5450'.
- Spot 18 cu. ft. Class B cement w/2% CaCl₂ @ 3547'. Mesa Verde plug 3345' - 3547'.
- Spot 40 cu. ft. Class B cement plug @ 2019'. Pictured Cliffs - Fruitland plug 1580' - 2019'.
- Perforate 4 1/2" casing @ 1305'. Break down perf @ 800 psi. Est. rate 2 BPM @ 500 psi. TIM with tubing to 1305'. Spot 101 cu. ft. class "B" with 4% gel @ 1305'. Displace cement to 1041'. Ojo Alamo plug 1041' - 1305'.
- Perforate 4 1/2" casing below surface casing @ 387'. Pump 166 cu. ft. class "B" cement w/4% gel - leaving 4 1/2" casing and 4 1/2" - 8-5/8" annular space full of cement.

Job complete 1-14-94.

07 JAN 26 PM 3:37
JAN 26 1994
JAN 26 1994

14. I hereby certify that the foregoing is true and correct

Signed John AlexanderTitle Operations ManagerDate 1/24/94

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

JAN 31 1994
DISTRICT MANAGER