

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator PAN AMERICAN PETROLEUM CORPORATION Lease O. H. Randel Well No. 1
 Location of Well: Unit L Sec. 9 Twp. 26N Rge. 11W County San Juan

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. or Csg.)
Upper Completion	Gallup	Oil	Art. Lift	Tbg.
Lower Completion	Dakota	Gas	Flow	Tbg.

PRE-FLOW SHUT-IN PRESSURE DATA

Upper Compl	Hour, date Shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)
	6-2-67	3 days	214	Yes
Lower Compl	Hour, date Shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)
	5-29-67	7 days	985	Yes

FLOW TEST NO. 1

Commenced at (hour, date)*		Pressure		Prod. Zone	Zone producing (Upper or Lower):
Time (hour, date)	Lapsed time since*	Upper Compl.	Lower Compl.	Temp.	Remarks
6-5-67	0 days	214	985		Both zones shut in.
6-5-67	1/2 day	22 gauge	985		Upper Flow/Lower Shut In.
6-6-67	1 day	22 gauge	987		" " " "
This test taken in two parts. First half ended July 6, 1967.					
Second half commenced July 18, 1967.					

Production rate during test

Oil: _____ BOPD based on _____ Bbls. in _____ Hrs. _____ Grav. _____ GOR _____
 Gas: _____ MCFPD; Tested thru (Orifice or Meter): _____

MID-TEST SHUT-IN PRESSURE DATA

Upper Compl	Hour, date Shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)
	7-18-67	3 days	213	Yes
Lower Compl	Hour, date Shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)
	7-18-67	3 days	958	Yes

FLOW TEST NO. 2

Commenced at (hour, date)**		Pressure		Prod. Zone	Zone producing (Upper or Lower):
Time (hour, date)	Lapsed time since **	Upper Compl.	Lower Compl.	Temp.	Remarks
7-21-67	0 days	213	958		Both zones shut in.
7-24-67	3 days	248	534		Upper Shut In/Lower Flow.
7-28-67	7 days	274	515		" " " "

Production rate during test

Oil: _____ BOPD based on _____ Bbls. in _____ Hrs. _____ Grav. _____ GOR _____
 Gas: _____ MCFPD; Tested thru (Orifice or Meter): _____

REMARKS: _____

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

Approved: 8-24 1967
 New Mexico Oil Conservation Commission

By A. R. Keswick

Title PETROLEUM ENGINEER DIST. NO. 3

Operator PAN AMERICAN PETROLEUM CORPORATION

Original Signed By: G. W. EATON, JR.

Title Area Engineer

Date August 22, 1967



NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3-hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired. Data may be requested on wells which have previously shown questionable data.

24-hour oil zone tests: all pressures, throughout the entire test shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.


8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Commission on Northwest New Mexico Packer Leakage Test Form Revised 11-1-58, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only). A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer Leakage Test Form with all deadweight pressure points taken indicated thereon. For oil zones, the pressure curve should also indicate all key pressure changes which may be reflected by the recording gauge charts. These key pressure changes should also be tabulated on the front of the Packer Leakage Test Form.

The form consists of a large grid of graph paper, divided into four main quadrants by a vertical line and a horizontal line. Each quadrant contains a grid of small squares, suitable for plotting pressure versus time curves. The grid is intended for recording data from the packer leakage tests described in the instructions above.

Packer bearings Test
 O.H. Runkel #1 - 1967
 11-9-26-11

2nd Half

1st Half



K&E
 12 X 20 TO THE INCH
 7 X 10 INCHES
 KRUPP & ESSER CO.
 MADE IN U.S.A.

Time / Days
 May 29, 1967

1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12