Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 078 430

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE I. Type of Well Oil Well Gas Weil 8. Well Name and No. U Other 2. Name of Operator ONL GOW. DUV. Nickson 11 9. API Well No. Robert R. Click

3. Address and Telephone No. 30-045-05924 10. Field and Pool, or Exploratory Area Suite 230 Pecan Creek. 8340 Meadow Rd. Dallas, TX 75231 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 214-369-4848 <u>Basin Dakota</u> 11. County or Parish, State 2180' FSL - 1190' FWL, Sec 11, T26N, R8W NMPM San Juan, NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonmeni Change of Plans Recompletion **New Construction** Subsequent Report Non-Routine Fracturing Plugging Back Water Shut-Off Casing Repair Final Abandonment Notice Altering Casing Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* This well was plugged and abandoned as follows on 08/01/94 - 08/03/94: Set CIBP @ 6520' KB Pressure test casing to 500# - Lost 25# in 5 minutes)70 Fariaington, Ni Cap CIBP with 5 sacks class "B" cement (6454' - 6520') Spot plug 5514' - 5639' KB Spot plug 3585' - 4196' KB (plug tagged) Spot plug 2454' - \$850' KB Spot plug 1229' - 1559' KB Spot plug surface - 322' KB Approved as to plugging of the well bore. Install dry hole marker Liability under bond is retained until surface restoration is completed. Note: All plugs class "B" neat cement. 14. I hereby certify that the foregoing is trate and correct Tide Agent (This splice for Federal or State office use)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.