

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-B1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-603-5033

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo Tribal "P"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Tecito Dome Penn. "D"

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

**NW/4 SE/4 Section 7,
T-26-N, R-18-W**

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 1980' FRL, Section 7, T-26-N, R-18-W

14. DEPTH

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5843' GL

6. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST PUMP SURVEY
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The Navajo Tribal "P" No. 2 was plugged and abandoned 11-24-75 as follows:

1. Set cement retainer at 2812' KB, loaded annulus and pressured to 1000 psi. Pumped 50 sacks Class "B" cement down tubing. Pressure increased to 4000 psi and held.
2. Spotted 55 sacks cement on top of cement retainer at 2807'.
3. Spotted Class "B" cement plug from 40' to surface.
4. Tied in 8-5/8" - 4-1/2" annulus and pumped in 25 sacks Class "B" Neat cement.
5. Drilled out 40' top cement plug.
6. Perforated 2' in 4-1/2" casing with 2 SPF at 1575'.
7. Set cement retainer on 2-3/8" tubing at 1550' and cemented with 90 sacks Class "B" Neat cement. Squeezed 16 barrels cement behind 4-1/2" casing. Dumped 15 barrels cement on top of retainer.
8. Spotted 60' plug in 4-1/2" casing.
9. Cut off casing, erected P&A marker and cleaned up location.

Location will be reseeded according to B.I.A. specifications.

MAR 31 1976

18. I hereby certify that the foregoing is true and correct

SIGNED

B. L. Hamilton

TITLE **Area Adm. Supvr.**

DATE **March 30, 1976**

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

G.P.O. : 1973- 780-622 /VIII- 148

