



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **SP**
Lease No. **078899**
Unit **Western**

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|--|--|----------|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF | |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | Sandoli Frec. | X |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 7, 1958

Well No. **2-A** is located **1980'** ft. from **N** line and **1980'** ft. from **W** line of sec. **8**

SE NW/4 Section 8
(1/4 Sec. and Sec. No.)

26-N
(Twp.)

11-W
(Range)

N44°E
(Meridian)

Undesignated
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is **6199** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

3-7-58 Total Depth 5477'. Clean Out T. D. 5420'.

Sandoli fractured Lower Gallup perforated intervals 5244'-5281' (2 sh./ft.) with 45,681 gallons oil and 40,000# sand. Breakdown pressure 2380#, maximum treating pressure 2475#, Average treating pressure 2475#. Injection Rate 43.2 bbls./min. Flush 5,250 gallons.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Products Company**

Address **Post Office Box 1545**

Farmington, New Mexico

ORIGINAL SIGNED BY: JOSEPH E. KREGER

By

Title **Petroleum Engineer**