

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE\*  
(Other instructions on reverse side)

Form approved  
Budget Office No. 42-R1424  
5. LEASE DESIGNATION AND SERIAL NO.

SF-075599-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL  GAS WELL  OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR  
EL PASO PRODUCTS COMPANY

8. FARM OR LEASE NAME  
Western A

3. ADDRESS OF OPERATOR  
Post Office Box 1560, Farmington, New Mexico 87401

9. WELL NO.  
2

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface  
1980'/N, 1980'/W, Section 8, Township 26 North, Range 11 West

10. FIELD AND POOL, OR WILDCAT  
Gallegos Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 8, T26N, R11W, NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
6189 GR

12. COUNTY, TERRITORY, DISTRICT, AND STATE  
San Juan New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF   
FRACTURE TREAT   
SHOOT OR ACIDIZE   
REPAIR WELL   
(Other)

PULL OR ALTER CASING   
MULTIPLE COMPLETE   
ABANDON\*   
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF   
FRACTURE TREATMENT   
SHOOTING OR ACIDIZING   
(Other)


REPAIRING WELL   
ALTERING CASING   
ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Start Operations 5-12-68.  
Finish Operations 5-21-68.

1. Load hole with mud laden fluid.
2. Squeeze Gallup perforations 5281' to 5141' 16 sx. cement.
3. Shoot pipe at free point 2980' and pull.
4. Spot 30 sx. cement plug 4% gel 3032' to 2887' in and out of stub.
5. Spot 30 sx. cement plug 4% gel 1543' to 1433' Across top of Platuriff.
6. Spot 30 sx. cement plug 4% gel 533' to 423' Base of Ojo Alamo.
7. Spot 10 sx. cement plug in top surface casing with welded marker in place.
8. Clean location.



RECEIVED  
JUL 3 1968

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

Original Signed By: Jim Payne

SIGNED \_\_\_\_\_ TITLE Agent DATE July 3, 1968

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: