

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650'N, 1650'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
SF 078001-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Huerfano Unit
8. FARM OR LEASE NAME
Huerfano Unit
9. WELL NO.
#13
10. FIELD OR WILDCAT NAME
West Kutz (PC)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 8, T-26-N, R-10-W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6579' DF

RECEIVED

SEP 24 1982

NOTES: Report results of multiple completion or zone change on Form 9-330.

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Circulate well with mud and spot a plug from TD (2148') to 2048'.
- 2) Spot a plug from 1850' to 1750' inside the 5½" casing.
- 3) Perforate the casing at 1315' and squeeze cement to 1080' behind the casing.
- 4) Spot a plug inside the casing to 1050'.
- 5) Perforate the 5½" casing at 164' and squeeze cement to the surface in the 5½" - 8 5/8 annular space.
- 6) Spot a plug from 164' to the surface inside the 5½" casing.
- 7) Install a dry hole marker.

RECEIVED

AUG 29 1984

Subsurface Safety Valve: Manu. and Type

OIL CON. DIV.

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

DIST. 3

SIGNED

Wm. D. Wells

TITLE

Production Engineer

DATE

September 17, 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

M. Millenbach
M. MILLENBACH

AREA MANAGER