

		X

(SUBMIT IN TRIPLICATE)  
**UNITED STATES**  
**DEPARTMENT OF THE INTERIOR**  
**GEOLOGICAL SURVEY**

Indian Agency \_\_\_\_\_  
**Navajo Tribal**  
Allottee \_\_\_\_\_  
Lease No. **14-20-603-2085**  
**Old Trading Post**

**SUNDRY NOTICES AND REPORTS ON WELLS**

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

**RECEIVED**  
JAN 18 1960  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**Old Trading Post**

**Farmington, New Mexico, January 14, 1960**

Well No. **2** is located **1880** ft. from **N** line and **660** ft. from **E** line of sec. **10**

**NE 1/4 of Section 10** **T-26N** **R-14W** **N.M.P.M.**  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Undesignated Gallup** **San Juan** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6153** ft. (RDB)

**DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

As a result of not obtaining a commercial oil well, we propose to plug and abandon Old Trading Post No. 2 as follows:

1. Spot 30 sack cement plug on bottom (approximately 360' of fill-up in casing) and squeeze with minimum pressure to cement off circumferential cut.
2. Cut off and pull recoverable 4-1/2" casing.
3. Spot 50 sack cement plug across casing stub to extend 50' down pipe and 100' up into open hole.
4. Spot 100 sack cement plug 1200-1450 across Pictured Cliffs formation.
5. Spot 10 sack cement surface plug 0-30' and erect Dry Hole Marker.
6. Fill hole with mud-laden fluid between cement plugs.
7. If pipe recovery is considerably less than 3500' the above plugging procedure may need to be modified.
8. Verbal approval for plugging procedure received from Mr. Shoger to Mr. Bauer January 13, 1960.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Pan American Petroleum Corporation**

Address **Box 487**

**Farmington, New Mexico**

Attn: **L.O. Speer, Jr.**

ORIGINAL SIGNED BY  
By **R. M. Bauer, Jr.**  
Title **Area Engineer**  
**RECEIVED**  
JAN 20 1960  
OIL CON. COM.  
DIST. 3

