




LOCATE WELL CORRECTLY

U. S. LAND OFFICE **Santa Fe**SERIAL NUMBER **078388**

LEASE OR PERMIT TO PROSPECT

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

Company **J. Glenn Turner** Address **Box 728 - Farmington, New Mexico**
Lessor or Tract **Ballard - Federal** Field **Wildcat** State **New Mexico**
Well No. **2-11** Sec. **11** T. **26N** R. **9W** Meridian **N.M.P.M.** County **San Juan**
Location **890** ft. **N.** of **N.** Line and **990** ft. **E.** of **E.** Line of **Sec. 11** Elevation **6187**
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed

Date **January 17, 1955****C. Benson Neal, Agent in Farmington**

The summary on this page is for the condition of the well at above date.

Commenced drilling **November 13,** 19**54** Finished drilling **December 15,** 19**54**

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from **1,900** to **1,943** No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
8-5/8"	24	8	C.F.I.	91.081	None				Surface
5-1/2"	14	8	C.F.I.	1,908	Halliburton				Long String
1"	11	8	C.F.I.	1,931	None				Production

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8-5/8"	92.081 g.l.	100	Halliburton		Mostly water
5-1/2"	1,897 g.l.	100	Halliburton		Mostly water

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____

Adapters—Material _____ Size _____

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
		O.W.B. nitro	80	12-15-54	1911-1943	1,943
		Treated with 6310 gal. diesel, 5300 gal. sand.		12-15-54	1908-1943	1,943

2268 gal. diesel. Breakdown pressure 100#. Treating: Max. 100#. Min. 800#. Injection 16.2 bbl/min

TOOLS USED

Rotary tools were used from **0** feet to **1,905** feet, and from _____ feet to _____ feet

Cable tools were used from **1,905** feet to **1,943** feet, and from _____ feet to _____ feet

Tested:

DATES

Shut in to await pipe line

December 30, 19**54**Put to producing **December 17,** 19**54**

The production for the first 24 hours was _____ barrels of fluid of which _____% was oil; _____% emulsion; _____% water; and _____% sediment. Gravity, °Bé. _____

If gas well, cu. ft. per 24 hours **582 mcf/d** (3 hour test) Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. **650 psig.**

EMPLOYEES

Benson-Martin - Rotary, Driller**McConnell, Incorporated - Cable**, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	1318	1318	Sand & Shale
1318	1804	486	Shale
1804	1905	101	Sand, Shale & Coal
1905	1943	38	Sand, Top Pictured Cliffs 1900

(OVER)

16-48094-3

FORMATION RECORD - CONTINUING

