

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐ JUN 22 1984  
2. NAME OF OPERATOR OIL CON. DIV.  
El Paso Natural Gas Company DIST. 3  
3. ADDRESS OF OPERATOR  
P. O. Box 289, Farmington, N. M. 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 800'N, 990'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED

JUN 22 1984

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE

SF 078388

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Huerfanito Unit

8. FARM OR LEASE NAME

Huerfanito Unit

9. WELL NO.

63

10. FIELD OR WILDCAT NAME

Ballard P.C.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 11, T26N, R9W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6187' DF

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10-27-81 1-Circulated well and pulled 1" tubing.

10-28-81 2-Trip in with 1 1/4" work string and spot a 25 sk plug to fill the open hole plus 100' of the 5 1/2" casing. (Top @1797')

3-Spot a 12 sk plug from 1652' to 1552'.

4-Perforate the 5 1/2" casing and squeeze cement from 1200' to 900' behind the casing (44 sks) and spot a plug from 1200' to 900' (35 sks) inside the casing.

10-29-81 5-Perforate the 5 1/2" casing at 142 ft. and squeeze cement in the 5 1/2-8 5/8" annular space to the surface (26 sks).

6-Spot a plug inside the 5 1/2" to surface from 142'.

7-Cut off wellhead and install dry hole marker.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*William D. Wall*

TITLE

Production Engineer

DATE

JUN 22 1984

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUN 22 1984

*James E. Edwards Jr.*  
AREA MANAGER