

X			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **SF**
Lease No. **078897**
Unit **Western**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	Sandoil Frac.	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 21, 19 57

Well No. 3 is located 660 ft. from N line and 660 ft. from E line of sec. 7NW 1/4 Sec. 7 26N 11W N.M.P.M.(1/4 Sec. and Sec. No.)
Undesignated
(Field)San Juan
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 6058 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

10-14-57. T.D. 5304'. Clean Out T.D. 5270'. Sandoil frac. 4 sh/ft perf. intervals 5146'-62 with 21,000 gal. oil & 20,000# sand. Brkdn pr. 2100#, max tr pr 2100#, average tr pr 1950#. Injection rate 66.6 bbls./min. Flush 11,760 gal. 10-25-57. T.D. 5304'. Temporary Bridge Plug at 5232'. Sandoil frac. 4 sh/ft. perf. intervals 5182-98; 5204-14 with 20,000 gal. oil & 20,000# sand. Brkdn press. 1500#, max tr pr 2100#, average tr pr 2075#. Injection rate 48.1 bbls./min. Flush 9,240 gal. 11-4-57. T.D. 5304'. Temporary Bridge plug at 5160'. Sandoil frac. 4 sh/ft perf intervals 5110-25; 5130-41 with 20,454 gal. oil & 20,000# sand. Brkdn pr 2100#, max tr pr 2100#, average tr pr 2000#. Injection rate 57.5 bbls./min. Flush 9,744 gal. 11-15-57 T.D. 5304. Temp. bridge plug at 5030'. Sandoil frac 4 sh/ft perf. Intervals 5006-20, with 20,000 gal (See back of page)

Company El Paso Natural Gas Products CompanyAddress P.O. Box 1565Farmington, New MexicoBy Van E. DykerTitle Petroleum Engineer

DETAILS OF WORK (Continued from page 1)

oil and 20,000# sand. Brkdwn pr 1900#, max tr pr 2400#, average tr pr 2350#. Injection rate 54.9 bbls./min. Flush 9,030 gallons.