

Form 9-331b  
(April 1952)

(SUBMIT IN TRIPLICATE)

Indian Agency Navajo

Tribe Navajo

Allottee Navajo "J"

Lease No. 14-20-403-20

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL	Report of Drill Stem Test No. 1	<input checked="" type="checkbox"/>
	Report of Drill Stem Test No. 2	<input checked="" type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 14, 1958

Navajo "J"  
Well No. 1 is located 530 ft. from N line and 530 ft. from E line of sec. 11

NE 1/4 - NE 1/4 Section 11  
(1/4 Sec. and Sec. No.)

26N  
(Twp.)

13W  
(Range)

N.M.P.M.  
(Meridian)

Mildred (Dakota)  
(Field)

San Juan  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 5925 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding points, and all other important proposed work)

**DRILL STEM TEST NO. 1 5856-5905'** 1" bottom hole choke & 1" top opening.  
Tool open 3 hrs. with weak blow of air throughout test. IFF 440', FFP 260',  
30 min. SIDHP 1676', Hyd. pressure in 2952', out 2910'. Recovered 477' of  
drilling mud.

**DRILL STEM TEST NO. 2 5957-6008'**  
Tool open 1 hr. & 25 min. with very weak blow of air for 40 min. & died.  
Recovered 90' of drilling mud. IFF 150', FFP 350', 30 min. SIDHP 1750',  
Hyd. pressure in 3000', out 3000'.

Ran & set 5 1/2" casing at 6063' & cemented with 300 sks. reg. cement & 300 cu. ft.  
of Stratacrete, 2% Gel.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SKELLY OIL COMPANY

Box 426

Address Farmington, New Mexico

By (Signed) P. E. Cosper

Title District Superintendent