

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
BURLINGTON RESOURCES OIL & GAS COMPANY

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
990' FSL, 1650' FWL, Sec. 2, T-26-N, R-9-W, NMPM, San Juan County

API # (assigned by OCD)
30-045-06004

5. Lease Number

6. State Oil&Gas Lease #
B-11122

7. Lease Name/Unit Name
Huerfanito Unit

8. Well No.
#17

9. Pool Name or Wildcat
Ballard Pict'd Cliffs

10. Elevation:

RECEIVED
JUN 15 1999
OIL CON. DIV.
DIST. 3

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

5-10-99 MIRU. ND WH. NU BOP. TOOHH w/1 1/2" tbg. TIH w/5 1/2" cmt retainer, set @ 1725'. PT csg to 500 psi, OK. Plug #1 w/57 sx Class "B" cmt, sqz 45 sx below to fill PC open hole & cover Fruitland top & fish. Spot 12 sx above to 1625'. TOOHH. TIH w/wireline. Perf 3 sqz holes @ 1245'. (Received approval from Henry Villanueva, NMOC, to spot inside plug @ 1462-1095' on 5-10-99). Plug #2 w/43 sx Class "B" cmt inside csg @ 1462-1095' to cover sqz holes & Kirtland/Ojo Alamo tops. Circ hole clean. TOOHH. SDON.

5-11-99 TIH w/wireline, tag cmt @ 1107'. Perf 3 sqz holes @ 152'. Est circ out bradenhead. Plug #3 w/71 sx Class "B" cmt dwn 5 1/2" csg @ 152' to surface. Circ 1 bbl cmt out bradenhead. Remove WH; cmt found dwn 90' in csg & annulus. Mix 48 sx Class "B" cmt to fill csg & annulus; install P&A marker. RD. Rig released.

SIGNATURE *[Signature]* Regulatory Administrator June 8, 1999

vkh

(This space for State Use)

ORIGINAL SIGNED BY E. VILLANUEVA

DEPUTY OIL & GAS INSPECTOR, DIST. #3

OCT 27 1999

Approved by _____ Title _____ Date _____