

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved,
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF-078953

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

J. W. Goddard

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Gallegos Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1-26N-12W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Skelly Oil Company

3. ADDRESS OF OPERATOR

1860 Lincoln Street- Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 660' FEL of Section 1-26N-12W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6021' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well reached the economic limit and no longer is profitable to operate.

Plans are to plug and abandon this well as follows:

- First Plug - Across Gallup Zone perms. 5247'-5108' filling up 50' to 5058'.
- Second Plug - 50' inside 5 1/2" casing and 50' above where casing is shot in two.
- Third Plug - 100' plug above top of Mesa Verde formation (unless production casing is left remaining through this zone).
- Fourth Plug - 100' plug at the bottom of Ojo Alamo Sand (unless surface casing is set through the Ojo Alamo Sand).
- 10 sacks of cement in top of surface casing with dry hole marker.

RECEIVED

NOV 22 1967

U. S. GEOLOGICAL SURVEY
SARASOTA, FLA.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

District Superintendent

DATE

Nov. 17, 1967

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: