



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 87 078933
Unit J. W. Goddard

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<u>Production</u>	<u>X</u>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING		
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING		
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR		
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT		
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY		
NOTICE OF INTENTION TO ABANDON WELL	<u>Report of Perforations</u>		<u>X</u>
	<u>Report of Sand-Oil Pressing</u>		<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 2, 1958

J. W. Goddard
Well No. 5 is located 1980 ft. from S line and 1980 ft. from W line of sec. 2
NE 1/4 SW 1/4 Section 2 36N 12W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated (Gallup) San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5891 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ran & set $5\frac{1}{2}$ " casing at 5125' & cemented with 125 sks. reg. cement & 125 cu. ft. stratacrete. Ran temperature survey by Lee King & found top of cement behind $5\frac{1}{2}$ " casing at 3714'.

Perforated $5\frac{1}{2}$ " casing 5069-70' w/4 Schlumberger jet shots to test cement job. Cement job tested O.K. Perforated $5\frac{1}{2}$ " casing 5057-69' w/4 Schlumberger jet shots per ft. Total perfs. 13', 52 holes.

Frased Gallup formation, down $5\frac{1}{2}$ " casing, thru $5\frac{1}{2}$ " casing perfs. 5057-70', w/25,000# 20-40 sand & 25,000 gals. lss. oil. MDP 2500#, Max. TP 1800#, Min. TP 1400#. Shut down pressure 700#. Inj. rate 41.7 BFM. Time of treatment 20 min.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SWPCO

Address 1000 4th St

By W. B. Goddard

Title District Superintendent