

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Merrion Oil & Gas Corporation

3. ADDRESS OF OPERATOR
P. O. Box 1017, Farmington, New Mexico 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL and 1980' FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☒

BUREAU OF LANDS
FARMINGTON

RECEIVED

JUL 23 1984

NOTE: Report results of multiple completion or zone change on Form 9-330.1

JUL 30 1984

OIL CON. DIV.

5. LEASE
SF 080384-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hickman A

9. WELL NO.

5

10. FIELD OR WILDCAT NAME

Gallegos Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3, T26N, R12W

12. COUNTY OR PARISH 13. STATE

San Juan New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5980' DF

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-20-84
Spotted 35 sx (41.3 cu. ft.) Class B cement from 5155 - 4845 to cover Gallup.
Spotted 35 sx (41.3 cu. ft.) Class B cement from 4100 - 3790' to cover Mesaverde - Mancos boundary.
Perforated casing at 2250. Placed 40 sx (47.20 cu. ft.) Class B cement inside and outside casing from 2250 - 2100' to cover Lewis - Mesaverde boundary.
Shot off casing at 1800'. Placed 25 sx (29.5 cu. ft.) Inside and outside stub as per verbal instructions from BLM.
Spotted 40 sx (47.20 cu. ft.) from 1400 - 1250 to cover Pictured Cliff.
Spotted 30 sx (35.40 cu. ft.) Class B From 850 - 750' to cover Fruitland top.
Spotted 47 sx (55.46 cu. ft.) Class B from 280 - 123 to cover Ojo Alamo - Kirtland boundary.
Placed 10 sx (11.8 cu. ft.) Class B surface plug and erected dry hole marker.
Placed 9.2 #/gal. mud between plugs.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John J. [Signature] TITLE Operations Manager DATE 7/23/84

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

NMOC