Form 9-331a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

## UNITED STATES

**DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY** 

Land Office	Santa Pe
Lease No	078135
Unit	NE/4

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	i ii
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	· 1
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.	
(INDICATE ABOVE BY CHECK	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	February 9, 1956 , 19
ME/4 Sec. 1 26 N. R (1/4 Sec. and Sec. No.) (Twp.)	
(Field) (Co	tan County or Subdivision)  (State or Territory)
	ETAILS OF WORK
copese to spud with cable tools; ctured Cliffs Formation - expect rface. Completion with cable to clidified nitro glycerin as condicating program: 90 feet of 8 surface, using at least 75 sack 5-1/2 0.D. 1 J-55 seamless remation cemented with 100 sacks 1* tubing to be set within 20 Notice of intention to drill	then drill with rotary tools to the top of the between 1,900 feet and 2,200 feet belocals - and sand oil fracturing or shooting witions warrant.  3-5/8" new 8 rd. thd., 21/2 casing, Circulate as of cement.
ropese to spud with cable tools; ctured Cliffs Formation - expect arface. Completion with cable to clidified nitro glycerin as condicating program: 90 feet of 8 surface, using at least 75 sack 5-1/2 0.D. 1 J-55 seamless remation cemented with 100 sacks: 1* tubing to be set within 20	then drill with rotary tools to the top of ted between 1,900 feet and 2,200 feet belowed serious warrant.  3-5/8" new 8 rd. thd., 21/2 casing, Circulate of casing to be set on top of Pictured Cliffs regular coment.  6-64 of total depth for production filed May 25, 1955, and approved.
ropese to spud with cable tools; ctured Cliffs Formation - expect arface. Completion with cable to didified nitro glycerin as condicating program: 90 feet of 8 surface, using at least 75 sack 5-1/2 0.D. 1 J J-55 seamless relation cemented with 100 sacks: 1* tubing to be set within 20 Notice of intention to drill tice for copies of plats.	then drill with rotary tools to the top of ted between 1,900 feet and 2,200 feet belowed serious warrant.  3-5/8" new 8 rd. thd., 21/2 casing, Circulate of casing to be set on top of Pictured Cliffs regular coment.  6-64 of total depth for production filed May 25, 1955, and approved.
ropese to spud with cable tools; ctured Cliffs Formation - expect arface. Completion with cable to didified nitro glycerin as condicating program: 90 feet of 8 surface, using at least 75 sack 5-1/2 0.D. 1 J J-55 seamless relation cemented with 100 sacks: 1* tubing to be set within 20 Notice of intention to drill tice for copies of plats.	then drill with rotary tools to the top of the between 1,900 feet and 2,200 feet belowed serious and sand oil fracturing or shooting witions warrant.  5-5/8" new 8 rd. thd., 2h/ casing, Circulate of cement.  casing to be set on top of Pictured Cliffs regular coment.  Feet of total depth for production.
copese to spud with cable tools; ctured Cliffs Formation - expect rface. Completion with cable to lidified nitro glycerin as condi Casing program: 90 feet of 8 surface, using at least 75 sack 5-1/2 0.D. 11/3 J-55 seamless rmation cemented with 100 sacks 1* tubing to be set within 20 Notice of intention to drill tice for copies of plats.  I understand that this plan of work must receive approximation.	then drill with rotary tools to the top of ted between 1,900 feet and 2,200 feet belo cols - and sand oil fracturing or shooting witions werrant.  3-5/8" new 8 rd. thd., 21/2 casing, Circulate as of cement.  casing to be set on top of Pictured Cliffs regular cement.  6-5/8, and approved., the that the color of the c
ropese to spud with cable tools; ctured Cliffs Formation - expect arface. Completion with cable to didified nitro glycerin as condicating program: 90 feet of 8 surface, using at least 75 sack 5-1/2 0.D. 11/4 J-55 seamless relation cemented with 100 sacks: 1* tubing to be set within 20 Notice of intention to drill tice for copies of plats.  I understand that this plan of work must receive approximation to drill intention to dril	then drill with rotary tools to the top of the between 1,900 feet and 2,200 feet belowed to the top of the between 1,900 feet and 2,200 feet belowed a sand oil fracturing or shooting witions warrant.  3-5/8" new 8 rd. thd., 21/2 casing, Circulate as of cement.  casing to be set on top of Pictured Cliffs regular cement.  I feet of total depth for product on filed May 25, 1955, and approval. See that