

*Certified Mail: 2202 722 848
Return Recpt. Requested.*

June 30, 1994

Page 1 of 1

STEPHEN H. KINNEY
FEDERAL #1 (PC)
790' FNL 990' FEL
Sec.3, T26N, R8W
San Juan County, NM
NM 020494

PLUG AND ABANDONMENT REPORT

Cementing Summary:

Plug #1 sxs Class B cement from 2210' to 1616' over Pictured Cliffs perms.

Plug #2 with 31 sxs Class B cement from 1625' to 1216' inside casing.

Plug #3 with 55 sxs Class B from 148' to surface, circulated 1 bbl good cement out bradenhead.

Plugging Summary:

6-28-94 Safety Meeting. Drive rig to location. Rig up. Lay relief lines. Casing pressure 300#. Blow well down. Pump 10 bbls water down casing to kill well. ND wellhead. NU BOP. Plug #1 with 45 sxs Class B cement from 2210' to 1616' over Pictured Cliffs perms. POH with tubing. Shut in well, WOC. SDFN.

6-29-94 Safety Meeting. Open up well; no pressure. Load well with 20 bbls water and pressure test casing to 500#, held OK. RIH and tag top of cement at 1822'. POH. Perforate 4 squeeze holes at 1570'. Attempt to establish rate into squeeze holes, pressured up to 800#. Procedure change on Plug #2 approved K. Schneider, BLM. Plug #2 with 31 sxs Class B cement from 1625' to 1216' inside casing. POH with tubing. Perforate 2 squeeze holes at 148'. Establish circulation out bradenhead with 12 bbls water. Plug #3 with 55 sxs Class B from 148' to surface, circulated 1 bbl good cement out bradenhead. Shut in well, WOC. ND BOP and cut off well head. Install P&A marker with 25 sxs Class B cement. Rig down and move off location.