ñay 1963)	DEPAR	UNITED STATE TMENT OF THE GEOLOGICAL SUF	INTERIOR	SUBMIT IN TRIPLICA (Other instructions on verse side)	16-	DESIGNATION	red. au No. 42-R14	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)					6. IF IND	IAN, ALLOPTE	E OR TRIBE NA	
I. OIL GAS [V]					7. UNIT A	7. UNIT AGREEMENT NAME		
WE'L WELL A OTHER 2. NAME OF OPERATOR						8. FARM OR LEASE NAME		
J. Gregory Merrion and Robert L. Bayless						Liberty Bell		
3. ADDRESS OF OPERATOR P.O. Box 1541, Farmington, New Mexico 87401						9. WELL NO.		
4. LOCATION OF WELL See also space 17 b	(Report locati	on clearly and in accordance	e with any State		1	AND POOL,	OR WILDCAT	
At surface	FNL and	1850 FWL			su:	cat T., R., M., OR RVEY OR ARE 5, T26	A	
14. PERMIT NO.		15. ELEVATIONS (Show		GR, etc.)	12. COUN	TY OR PARIS	H 13. STATE	
		58	873 GR		San	Juan	N.M.	
16.	Check	Appropriate Box To I	ndicate Natui					
	NOTICE OF I	NTENTION TO:		SUI	BSEQUENT REPOR	T OF:		
TEST WATER SHUT	T-OFF	PULL OR ALTER CASING MULTIPLE COMPLETE		WATER SHUT-OFF FRACTURE TREATMENT		REPAIRING ALTERING		
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING		ABANDONM	ENT* X	
REPAIR WELL (Other)		CHANGE PLANS		(Other)	aults of multin	e completion	on Well	
17 ACCORDED DECEMBER	O OR COMPLETE	o OPERATIONS (Clearly State	all pertinent det	(NOTE: Report re Completion or Rec	completion Repo	estimated da	orm.)	
17. DESCRIBE PROPOSED proposed work, nent to this work and the second sec	If well is di k.) *	Ojo Alamo 375-5	Ventures. rval. Pulsax cement 50; 10 sax	Completion or Rectalis, and give pertinent dand measured and true v	sax cement approxim tub; 200 for and top	estimated dror all market to covulately 5t. plug of 10-3	er 50 ft. across /4"	
proposed work. nent to this work	If well is di k.) *	Moved in L & M perforated inte and spotted 10 Ojo Alamo 375-5 surface casing.	Ventures. rval. Pulsax cement 50; 10 sax	Completion or Rectalls, and give pertinent dand measured and true versions. Pumped in 20 stated casing from the plug across state plug at bottom dry hole marker	sax cement approxim tub; 200 for and top	estimated dror all markets to cover the cover to cover the cover t	er 50 ft. across /4"	
proposed work. nent to this work Aug. 03	If well is di	Moved in L & M perforated inte and spotted 10 Ojo Alamo 375-5 surface casing.	Ventures. rval. Pulsax cement 50; 10 sax	Completion or Rectalls, and give pertinent dand measured and true versions. Pumped in 20 stated casing from the plug across state plug at bottom dry hole marker	sax cement approximately; 200 for and clear	estimated dror all markets to cover the cover to cover the cover t	er 50 ft. across /4"	

APPROVED IN CONDITIONS OF APPROVING A PROVINCE DATE . JAMES F. SIMS
DISTRICT ENGINEER **NMOCC**

*See Instructions on Reverse Side