

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

RECEIVED
MAR 3 1 1998

TX-276

2. Name of Operator

OIL CON. DIV.
BURLINGTON
RESOURCES
OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

990' FSL, 1795' FWL, Sec. 16, T-27-N, R-8-W, NMPM, San Juan County

API # (assigned by OCD)
30-045-06449

5. Lease Number

6. State Oil & Gas Lease #
E-6634

7. Lease Name/Unit Name

Schultz

8. Well No.

3

9. Pool Name or Wildcat
So. Blanco Pict. Cliffs

10. Elevation:

Type of Submission

___ Notice of Intent
X Subsequent Report
___ Final Abandonment

Type of Action

___ Abandonment
___ Recompletion
___ Plugging Back
___ Casing Repair
___ Altering Casing
X Other - Restimulate
___ Change of Plans
___ New Construction
___ Non-Routine Fracturing
___ Water Shut off
___ Conversion to Injection

13. Describe Proposed or Completed Operations

- 2-17-98 MIRU. ND WH. NU BOP. TIH, release pkr. TOOH w/68 jts 2 3/8" tbgs & pkr. TIH w/4 3/4" bit. SDON.
- 2-18-98 Tag fill @ 2138'. Blow well & CO to 2203'. Drill open hole to new TD @ 2320'. Circ hole clean. TOOH. SDON.
- 2-19-98 (Have water flow, verbal approval to continue from Johnny Robinson, OCD). TIH w/75 jts 3 1/2" 9.2# J-55 csg, set @ 2302'. Pump 100 sx Class "G" neat cmt w/2% Econolite, 5 pps Gilsonite, 0.25 pps Celloflake (206 cu.ft.). Tailed w/50 sx Class "B" neat cmt w/1% Econolite, w/5 pps Gilsonite, 0.25 pps Celloflake (74 cu.ft.). Displaced w/20 bbl wtr. Circ 10 bbl cmt to surface. WOC. ND BOP. NU WH. RD. Rig released.
- 3-3-98 MIRU. PT 3 1/2" csg to 5000 psi, OK. Perf lower Pictured Cliffs w/1 SPF @ 2203, 2206, 2214, 2218, 2224, 2228, 2234, 2238' w/8 0.31" diameter holes total. Spot 8 gal 15% Hcl & 12 gal 28% Hcl. Reperf holes @ 2234 & 2238'. Spot 4 gal 28% Hcl @ 2224'. Perf upper Pictured Cliffs w/1 SPF @ 2160, 2164, 2170, 2174, 2178, 2184, 2187, 2191, 2195, 2199' w/10 0.31" diameter holes total. Acidize w/500 gal 15% Hcl SDON.
- 3-4-98 Frac Pictured Cliffs w/361 bbl 20# linear gel, 181,640# 20/40 Arizona sd, 369,000 SCF N2. CO after frac.
- 3-5/6-98 Blow well & CO. SD.
- 3-7/15-98 SD.
- 3-16/26-98 Blow well & CO.
- 3-27-98 Blow well & CO. ND BOP. NU WH. RD. Rig released.

SIGNATURE
no

Regulatory Administrator March 30, 1998

(This space for State Use)

Approved by

Title

DEPUTY OIL & GAS INSPECTOR, DIST. #3

Date

MAR 3 1 1998