NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

| | Indicate Nature of Report by Checking B | elow | |
|--|--|---|---|
| REPORT ON BEGINNING DRILLING OPERATIONS | REPORT ON RESULT OF TEST OF CASING SHUT-OFF | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF PLUGGING WELL | REPORT ON RECOMPLETION OPERATION | REPORT ON (Other) | |
| | April 16, 1955 | Farmington, New | • |
| Following is a report on the work done | and the results obtained under the heading | noted above at the | |
| Frank A. Schultz, Jr. | | State | |
| (Company or Operator) | | (Lease) | ••••••• |
| Huerfanito Frilling Co., I | nc. , Well No | in the SW 1/4 NE 1/4 of | Sec 16 |
| 27-N, R. 8-W, NMPM., So. Bl | | | |
| he Dates of this work were as folows: | e11 7th & 8th, 1955 | | |
| | C-101 | | |
| otice of intention to do the work (was) (was | submitted on Form G 100 on | erch 26, 1955 | , 19 |
| | | , | |
| | | · · · · · · · · · · · · · · · · · · · | |
| DETAILED A Spudded well at 3:00 P.M. or 97° from ground. Ran t | men obtained. ACCOUNT OF WORK DONE AND RESU on April 7, 1955. Prilled to hree joints of 8-5/8" OD 21# | ULTS OBTAINED o total depth of 105° for J=55 casing to total depth | rom K.B., |
| DETAILED A Spudded well at 3:00 P.M. or 97° from ground. Ran to On April 8th, cemented with cement to surface. | on April 7, 1955. Prilled three joints of 8-5/8" OD 24# | ults obtained o total depth of 105' for J-55 casing to total de O sacks "Peamix S". Circ | rom K.B., pth. culated |
| DETAILED A Spudded well at 3:00 P.M. or 97' from ground. Ran to On April 8th, cemented with cement to surface. | men obtained. ACCOUNT OF WORK DONE AND RESU on April 7, 1955. Prilled to hree joints of 8-5/8" OD 21# | ults obtained o total depth of 105' for J-55 casing to total de O sacks "Peamix S". Circ | rom K.B., epth. culated |
| DETAILED A Spudded well at 3:00 P.M. or 97' from ground. Ran to On April 8th, cemented with cement to surface. | on April 7, 1955. Prilled three joints of 8-5/8" OD 24# | ults obtained o total depth of 105' for J-55 casing to total de O sacks "Peamix S". Circ | rom K.B., pth. culated |
| DETAILED A Spudded well at 3:00 P.M. or 97° from ground. Ran to On April 8th, cemented with cement to surface. | on April 7, 1955. Prilled three joints of 8-5/8" OD 24# | ults obtained o total depth of 105' for J-55 casing to total de O sacks "Peamix S". Circ | rom K.B., epth. culated |
| Spudded well at 3:00 P.M. or 97' from ground. Ran to On April 8th, cemented with cement to surface. Moved cable tool rig off. | ACCOUNT OF WORK DONE AND RESION April 7, 1955. Filled to hree joints of 8-5/8" OD 2h# h 50 sacks neat cement and 50 Awaiting rotary rig to cont. Huerfanito Frilling | o total depth of 105' for J-55 casing to total depth of sacks "Permix 8". Circle inue drilling 4/8/59 | rom K.B., epth. culated |
| Spudded well at 3:00 P.M. or 97° from ground. Ran to On April 8th, cemented with cement to surface. Moved cable tool rig off. | on April 7, 1955. Drilled to hree joints of 8-5/8" OD 21# h 50 sacks neat cement and 50 Awaiting rotary rig to continuous of the continuous con | o total depth of 105' fr J-55 casing to total de O sacks "Peamix S". Circ inue drilling 4/8/59 | com K.B., spth. sulated |
| Spudded well at 3:00 P.M. or 97° from ground. Ran to On April 8th, cemented with cement to surface. Moved cable tool rig off. | ACCOUNT OF WORK DONE AND RESION April 7, 1955. Drilled to hree joints of 8-5/8" OD 21/4" h 50 sacks neat cement and 5. Awaiting rotary rig to cont: Huerfanito Drilling (Company) I hereby certify the | o total depth of 105' for J-55 casing to total depth of sacks "Peamix 8". Circle interest of the company, Inc. Tool | rom K.B., spth. culated |
| Spudded well at 3:00 P.M. or 97° from ground. Ran ton April 8th, cemented with cement to surface. Moved cable tool rig off. Vitnessed by | ACCOUNT OF WORK DONE AND RESION ACCOUNT OF WORK DONE AND RESION APPRIL 7, 1955. Drilled to hree joints of 8-5/8" OD 21. hree joint | o total depth of 105' for J-55 casing to total depth of sacks "Peamix 8". Circle interest of the company, Inc. Tool | Pusher. |
| Spudded well at 3:00 P.M. or 97° from ground. Ran to On April 8th, cemented with cement to surface. Moved cable tool rig off. Witnessed by Oliver E. Towell (Name) Approved: OIL CONSERVATION COMM | ACCOUNT OF WORK DONE AND RESION ACCOUNT OF WORK DONE AND RESION April 7, 1955. Drilled to hree joints of 8-5/8" OD 21. hree joints | o total depth of 105' fr J-55 casing to total de 0 sacks "Peamix S". Circ inue drilling 4/8/59 Company, Inc. Tool | Pusher. |

| OIL CONSERVATOR AZTEC DISTANCE No. Copies Received DISTANCE Operator Salta Company Operator Transporter File | SION |
|--|----------|
| | |
| | |