

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

**Sundry Notices and Reports on Wells**

<p>1. <b>Type of Well</b> GAS</p> <hr/> <p>2. <b>Name of Operator</b> <b>MERIDIAN OIL</b></p> <hr/> <p>3. <b>Address &amp; Phone No. of Operator</b> PO Box 4289, Farmington, NM 87499 (505) 326-9700</p> <hr/> <p>4. <b>Location of Well, Footage, Sec., T, R, M</b> 1675' FNL, 1675' FEL, Sec. 16, T-27-N, R-8-W, NMPM, San Juan County</p>	<p>API # (assigned by OCD) 30-045-06521</p> <p>5. <b>Lease Number</b> E-6634</p> <p>6. <b>State Oil &amp; Gas Lease #</b> E-6634</p> <p>7. <b>Lease Name/Unit Name</b> Schultz</p> <p>8. <b>Well No.</b> 1</p> <p>9. <b>Pool Name or Wildcat</b> So Blanco Pictured Cliff</p> <p>10. <b>Elevation:</b></p>
---	--

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

**13. Describe Proposed or Completed Operations**

4-24-95 MIRU. ND WH. NU BOP. Could not released pkr. TIH w/1.390" cutter, cut tbg @ 2043'. POOH. (Verbal approval to change plans from Johnny Robinson, NMOCD). TOOH w/63 jts 1 1/2" tbg. TIH w/5 1/2" gauge ring to 2000'. TOOH. SDON.

4-25-95 TIH w/5 1/2" cmt retainer, set @ 1963'. Establish injection. PT on csg failed. Plug #1: pump 40 sx Class "B" cmt below cmt retainer. Plug #2: pump 33 sx Class "B" cmt above cmt retainer @ 1679-1963'. TOOH to 1401'. RU, perf 4 sqz holes @ 1450'. RD. TIH w/5 1/2" cmt retainer, set @ 1401'. Establish injection. PT on csg failed. Plug #3: pump 58 sx Class "B" cmt outside csg below cmt retainer @ 1275-1450'. Pump 20 sx Class "B" cmt on top of cmt retainer to 1229'. TOOH. RU, perf 2 sqz holes @ 155'. RD. Establish circ down csg & out bradenhead w/2 bbl wtr. Plug #4: pump 75 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. SDON.

4-26-95 ND BOP. Cut off WH. Pump 12 sx Class "B" cmt to fill 5 1/2" csg. Install dry hole marker w/8 sx cmt. RD. Well plugged and abandoned 4-26-95.

SIGNATURE *Peggy Marshall* Regulatory Affairs May 2, 1995

(This space for State Use)

Approved by *Johnny Robinson* **DEPUTY OIL & GAS INSPECTOR, DIST. 2**

**MAY - 3 1995**

**RECEIVED**  
**MAY - 3 1995**  
**OIL CON. DIV.**  
**DIST. 2**

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_