STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT This form is not to

be used for reporting

packer leakage tests in Southeast New Mexico

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	BURLINGTON RESOUR	CES OIL & GAS CO.	Lease DAY B		Well No. 2		
Location of Well:	Unit M Sect NAME O	07 Twp. 027 F RESERVOIR OR POOL	N Rge. 008W TYPE OF P (Oil or G				
Upper Completion	PICTURED CLIFFS		Gas	Flow	Tubing		
Lower Completion	MESAVERDE		Gas	Flow	Tubing		
Upper Completion	Hour, date shut-in 06/12/2000	PRE-FLOW SHUT-IN PRESSURE DATA Length of time shut-in SI press. psig 72 Hours 139		Stabilized? (Stabilized? (Yes or No)		
Lower Completion	06/12/2000	24 Hours		201	÷		
Commona	d at (have data)#		LOW TEST NO. 1				
TIME	d at (hour,date)* LAPSED TIME	06/13/2000 PRESSURE			OWER		
(hour,date)	SINCE*	Upper Completion Low	er Completion TE	MP RE	MARKS		
6/14/200	48 Hours	142	169				
6/15/200	72 Hours	143	160	12 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			
				RECEIVED ON CONTROL OF THE PROPERTY OF THE PRO	7202		
Production rat	e during test			Augus S	9 d 2		
Oil:	BOPD based on	Bbls. in	Hours.	Grav.	GOR		
Gas:		MCFPD; Tested thru (Orifice	e or Meter):				
		MID-TEST	SHUT-IN PRESSURE DAT	^A			
Upper Completion	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)		
5118702 313	· · · · · · · · · · · · · · · · · · ·	(Con	tinue on reverse side)		··· <u>·</u>		
		FAILED					

FLOW TEST NO. 2

Commenced at (hour, da	ate)**			Zone producing (Upper or Lower):			
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	REMARKS		
		Upper Completion	Lower Completion	TEMP.	REMARKS		
		ļ					
	ļ						
	1						
Production rate du	ring test						
Oil:	B	OPD based on	Bbls. in	Hours	GravGOR		
Gas:		MCFPI	D: Tested thru (Ori	ifice or Meter):			
Remarks:							
		· · · · · · · · · · · · · · · · · · ·					
I hereby certify that	at the information h	erein contained is true	e and complete to t	he best of my knowledge	e.		
Approved	. <u>.</u>	1	9	Operator Burlingto	n Resources		
New Mexico O	oil Conservation Div	vision		By Alaro L	Roy		
Ву				Title Operations Associate			
Title				Date Monday, June 26, 2000			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- I A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)