STATE OF NEW MEXICO

ENERGY and MINERALS DEPARTMENT Location of Well: N082708 Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:SCHWERDTFEGER A LS 014

Me	ter #:74674	RTU	:	C	County:SAN	JUAN	
	NAME RESE	CRVOIR OR POOL		TYPE PROD	METHOD PRO	DD MEDIUM PROD	
UPR COMP	SCHWERDTFE	GER A LS 014 P	C74674	GAS	FLOW	TBG	
LWR COMP	SCHWERDTFEGER A LS 014 MV72139			GAS	FLOW	TBG	
	.	PRE-FLO	W SHUT-IN	PRESSURE DA	TA		
	Hour/Date	e Shut-In Len	gth of Tim	e Shut-In	SI Press.	PSIG Stabilzed	
UPR COMP	09/12/94		72 hm		183	4	
LWR COMP	09/12/94		72 mo		243	Y	
	.		FLOW TEST	DATE NO.1		,	
Comme	nced at (ho	our,date)*		Zone P	Zone Producing (Upr/Lwr)		
		LAPSED TIME SINCE*	ME PRESSURE Upper Lower		Prod Temp.	REMARKS	
09/12/94		Day 1	178	256		Both Zones SI	
09/13/94		Day 2	180	238		Both Zones SI	
09/14/94		Day 3	182	241		Both Zones SI	
09/15/94		Day 4	183	243		From Lower Zone	
09/16/94		Day 5	185	240		· · · · · · · · · · · · · · · · · · ·	
09/17/94		Day 6	188	268		<u>н</u> к о	
Produ Oil: Gas:		MECE	D:Tested t	BBLs in theu (Orific N PRESSURE	ce or weccr	Grav GOR):METER	
UPR COMP LWR COMP	Hour, Dat	e SI Length o	of Time SI	SI Press	. PSIG St	abilized (yes/no) ECEIVED SEP 2 1 1994	
		(Co	ontinue on	reverse si	de) 0	HL CON. DIV.	

Commonand of flour, o		~~~	FLOW TEST I	NO. 2	•	
	7	· · · · · · · · · · · · · · · · · · ·		Zone producing (Upper or Lower)		
TIME frour, detail	LAPSED TIME SINCE ##		SURE	PROD. ZONE		
		Upper Completion	Lewer Completion	TEMP.	REMARKS	
			1			
	<u> </u>		l			
			Í			
				The state of the s	50 d. d	
	•					
tognetiou tate q	-					
il:	ВОРІ	D based on	D.I. :-	•		
			DOIS. IN _	Hours.	Grav GOR	
25:	· · · · · · · · · · · · · · · · · · ·	MCFF	D: Tested thru (Orifice or Meter):	:	
emarks:			•	,		
						
netern cetting th	at the informatio	a hereia containe	d is true and com	plete to the best	of my knowledge.	
pproved A	UG 2 1 19'	471				
	Conservation Di		. 19 Op	erator An	moco Production Company	
	,,	$\Lambda \Lambda$	D.,	31	heni Bradshaw &	
	arles Sh		D,			
			Tid	eFi	eld Tech	
de DEPUTY O	IL & GAS INSPECT	TOO DICT WA				
Te	IE & ONS HISTECT	IUK, DI31. #3	- Dat	<u> </u>	-20-94	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been directed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packet leakage text shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more shan seven days......
- 4. For Plow Text No. 1, one lone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such text shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage text, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 3. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced 2000 shall remain shut in while the 2000 which was previously shut in is produced.
- 7. Pressures for gas-zone term must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours term: immediately prior to the beginning of each flow-period, at fateen-manute intervals during the first hour thereof, and a houtly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 3-day term: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable tert data.

24-hour oil zone teru: all pressures, throughout the entire tert, shall be continuously measured and recorded with recording pressure gauges the securacy of which must be checked at least twice, once at the beginning and once at the end of each tert, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being gauge taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Astee District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packet Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).