Location of Well: NC82708 Page 1

## OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	tor: AMOCO ter #:74674		N COMP RTU:			HWERDTF County:S			014
	NAME RESE	RVOIR OR	POOL		TYPE PROD	METHOD	PROD	ME	DIUM PROD
UPR COMP	SCHWERDTFE	GER A LS	014 PC	74674	GAS	FLOW		TBG	
LWR COMP	SCHWERDTFEGER A LS 014 MV			72139 GAS		FLO	FLOW		TBG
		PR	E-FLOW	SHUT-IN	PRESSURE DA	TA		·	
	Hour/Date Shut-In			Length of Time Shut-In			ss. PS	IG	Stabilzed
UPR COMP	05/19/95			72 HES	193			150	
LWR COMP	05/19/95			Da HE.		217		125	
	.			FLOW TEST	DATE NO.1			'	
Comme	nced at (ho	our,date)*	5-19	-95 9:15		Zon	ie Prodi	ucir	ng (Upr/Lwr)
TIME (hour, date)		LAPSED TIME SINCE*		PRESSURE Upper Lower		Pro	- 1	REMARKS	
05/19/95		Day 1		124	189			Both Zones SI	
05/20/95		Day 2		148	193		I	Both Zones SI	
05/21/95		Day	3	157	203		I	Both	n Zones SI
05/22/95		Day	4	160	215	-	Fus	usla	Swer Zowe
05/23/95		Day	5	170	192		15		(1 )
05/24/95		Day	6	17)	189		,,		
Produ Oil: Gas:	oction rate	during te BOPD	based	on O:Tested t	BBLs in	Hrs	eter):M	Grav ETE	vGOR R
Gas.			MID-TI	EST SHUT-I	N PRESSURE	DATA	eren oa wii owo	* * * * * *	Mark the second of the second
UPR COMP	Hour, Date	e SI Ler	igth of	f Time SI	SI Press	. PSIG	Stabi	lize	ed (yes/no)
LWR COMP							id jek	7.5	1.000
S	) LARGO	) -5/B	(Co:	ntinue on	reverse si	de)	(i) <u>July</u> (i)		a Diw,

FLOW TEST NO. 2

, o	al Pour, de	le)		Zero :roduoing (Upper or Lower):				
		LAPSED TIME	PRESSURE		PROD ZONE			
	delej	BINCE * *	Upper Completion	Lower Completion	TEMP.	REMARKS		
		<b></b>						
			ł			!		
		ļ	<u> </u>					
					ļ			
	<del></del>							
				1				
		ļ						
Producti	on sate d	uring test				•		
Oil:		ВОР	D based on	Bbls. ir	· Hours	Grav GOR		
G25:			MCI	PD: Tested thru	(Orifice or Meter	r):		
						,		
(CIIIZIA)	•		· · · · · · · · · · · · · · · · · · ·					
<del>-</del>								
hereby	certify d	hat the informati	on perein contain	ned is true and co	emplete to the be	st of my knowledge.		
A norowa	ا ر	chnny Rolies	sen	10 (	<b>Dance</b>	Amoco Production Company		
New 1	Mexico O	Conservation I	Division	1y (	Operator	Anoco Froduction company		
• • • •		JUN 05 19	95	i	Зу	Theris Bradshaw &		
Зу	1			7	Ticle	Field Tech		
7	DEF	PUTY OIL & GAS IN	SPECTOR		· · · · · · · · · · · · · · · ·			
īide _				I	Date	6/2/95		

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after acrual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or themsal or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been districted. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packet leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one fone of the dual completion shall be produced at the normal are of production while the other zone remains shut-in. Such test shall be continued for even days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the autosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone testi all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is gas old or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas 200es only) and gravity and GOR (oil 20nes only).