



(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 07346
Unit Filen

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Water Proc.</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 29, 1960

Well No. 5 (NE) is located 650 ft. from S line and 620 ft. from W line of sec. 5

SW/4 Sec. 5 27N 2E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Blanco M. V. & Dakota Wildcat San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6243 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

6-9-60 T.D. 7035'. C.C.T.D. 6930'. Perf. Dakota 6702-6800; 6848-54; 6862-66; 6878-98
fraced with 70,000 gallons water and 80,000# sand. MD pr. 3200#, max. pr. 3500#,
avg. tr. pr. 3000#. I.R. 55.2 BHM. Flushed w/11,700 gallons water. Dropped 3 sets
of 20 balls and 1 set of 15 balls. 300 gallons 7/8" MDA spotted prior to fracing.
All water contained 1% Calcium Chloride and 7% J-98/1000 gal.
6-12-60 T.D. 7035'. Temp. BP set at 4950'. Perf. Point Lockout 4710-28; 4736-60;
4772-82; 4810-20; 4840-44; fraced w/43,176 gallons water, 45,000# sand, flushed
w/8400 gallons water. MD pr. 1400#, max. pr. 1500#, avg. tr. pr. 1400#. Avg.
I.R. 69 BHM. Dropped 5 sets of 20 balls and 1 set of 10 balls.
6-16-60 Re-perf. Point Lockout as above, fraced with 50,000 gallons water, 50,000#
sand. Flushed with 8100 gallons water. Max. pr. 3200#, MD pr. 2300#, avg. tr. pr.
2900#. Avg. I.R. 55 BHM. Dropped 3 sets of 25 balls each.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997

Farmington, New Mexico

By ORIGINAL SIGNED B.H. MEANS

Title Petroleum Engineer