(1	Feb. 1	'eb. 1961)				

Form 9-881a

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land	Office Senta Fe
Lonso	No. 078461
Unit .	Film

Well No. 5 (ND) is located 350 ft. from S line and S.W./A S.W./A Sec. 5 27 N S N NAME (General Well and Sec. No.)  Well No. 5 (ND) is located 350 ft. from S line and S.W./A S.W./A Sec. 5 27 N S N NAME (Merdian)  Compty or Subdivision)  The elevation of the derrick floor above sea level is S.W./A S.W./A Sec. 5 10 (State names of and expected depths to objective sands; show aliaes, weights, and langths of proposed casings; indicate mudding in points, and all other important proposed work)  Compty or Subdivision (State names of and expected depths to objective sands; show aliaes, weights, and langths of proposed casings; indicate mudding in points, and all other important proposed work)  Compty or Subdivision (State names of and expected depths to objective sands; show aliaes, weights, and langths of proposed casings; indicate mudding in the stage of the stage casing (State names of and expected depths to objective sands; show aliaes, weights, and langths of proposed casings; indicate mudding in the stage of the stage casing (State names of and expected depths to objective sands; show aliaes, weights, and langths of proposed casings; indicate mudding in the stage of the stage casing (State names of and expected depths to objective sands; show aliaes, weights, and langths of proposed casings; indicate mudding in the stage of the stage casing (State name) (State names of and expected depths to objective sands; show aliaes, weights, and langths of proposed casings; indicate mudding in the stage of the stage	SUBSCOUENT REPORT OF SHOOTING OR ACIDETING.  INCE OF INTENTION TO TEST WATER SHUT-OFF.  INCE OF INTENTION TO SHOOT OR ACIDIZE.  INCE OF INTENTION TO SHOOT OR ACIDIZE.	NOTICE OF INTENTION TO CHANGE PLANS.  NOTICE OF INTENTION TO TEST WATER SHUT-OFF.  NOTICE OF INTENTION TO RECORLL OR REPAIR WELL.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **SUBSCOURT REPORT OF ABANDONMENT.  SUPPLEMENTARY WELL HISTORY.  NOTICE OF INTENTION TO DULL OR ALTER CASING.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA  **June 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DA	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY SUPPLEMENTARY WELL HISTORY SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO REDRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  Jame 30  Well No. 9 (ND) is located 350 ft. from Siline and ft. from Willine of sec S.W./A S.W./A Sec. 5 27 II S W II.M.P.M.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  Jame 30  Well No. 9 (ND) is located 350 ft. from Siline and Market Mark	Subsequent report of Altering Casing Subsequent report of Altering Casing Subsequent report of Report of Repair Subsequent report of Report of Repair Subsequent report of Report of Report of Repair Subsequent report of Report	NOTICE OF INTENTION TO TEST WATER SHIT-OFF.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JULY 30	SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY  E OF REPORT, NOTICE, OR OTHER DATA)
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL  NOTICE OF INTENTION TO SHOOT OR ACIDIZE  NOTICE OF INTENTION TO SHOOT OR ACIDIZE  NOTICE OF INTENTION TO PULL OR ALTER CASING  NOTICE OF INTENTION TO PULL OR ALTER CASING  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  Anne 30  Vell No. 5 (ND) is located 350 ft. from S line and ft. from W line of sec  S.V./A S.W./A Sac. 5 27 H S W	NO. 5 (NE) is located 350 ft. from S line and ft. from Wiles and Isc. 5 27 8 8 8 8.M. P.N.  NO. 5 (NE) is located 350 ft. from S line and ft. from W line of sec	MOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  AND 30  [VIII]  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  AND 30  [VIII]  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, OR OTHER DATA)  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, OR OTHER DATA)  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, OR OTHER DATA)  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  [VIII]  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  [VIII]  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  [VIII]  AND 30  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  [VIII]  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY  G G G G G G G G G G G G G G G G G G G
NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO ABANDON WELL  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  Jane 30  Vell No. 9 (ND) is located 350 ft. from S line and ft. from W line of sec S.W./A S.W./A Sac. 5 27 H S W H.M.P.M.  (We See and See No.) (Twp.) (Range) (Meridian)  (Field) (County or Subdivision) (State or Territory)  The elevation of the derrick floor above sea level is 543 ft.  DETAILS OF WORK  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding in points, and all other important proposed work)  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding in points, and all other important proposed work)  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding in points, and all other important proposed work)  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding in points, and all other important proposed work)  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding in points, and all other important proposed work)  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding in points, and langths of proposed work)  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed work)  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed work)  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed work)  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed work)  Itate names of and expected depths to objective sands; show sizes, weights, and langths of proposed work)	Supplementary well history  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  June 30  No. 5 (ND) is located 50 ft. from S line and 30 ft. from W line of sec.  (A S.W. /A Sec. 5 27 H S W H.M.P.N.  (Kango) (Merdian)  So M.V. Dekorts Wildoxt Sen June  (County or Subdivision)  (Pield)  (County or Subdivision)  (State or Territory)  celevation of the derrick floor above sea level is 5243 ft.  DETAILS OF WORK  Summers of and expected depths to objective anades show dians, weights, and linesths of proposed casings; indicate mudding jobs, cemes ing points, and all other important proposed work)  3-50. Total Dayth 7035. Ram 39 fts. (569') 7", 23 H-80 casing. 160 fts.  3-7 23 3, J-55 casing. 25 fts. (258') 7" 23 H-80 casing. 160 fts.  3-10 casing total 224 fts.  3-20 casing total 224 fts.  3-20 casing total 225 fts.	NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO ABANDON WELL.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  June 30  [Vell No. 5 (MD) is located 350 ft. from [N] line and 320 ft. from [W] line of sec.  [N. /A S. W. /A S. W. /A S. S. 5 27 N N N N. P. N.  (C. Sec. and Sec. No.)  (State or Territory)  (State or Territory  (State or Territory)  (State or Territory)  (State or Territory  (State or Territory)  (State or Territory)  (State or Territory  (State or Territory)  (State or Territory)  (State or Territory  (State or Territory)  (State or Terr	EUPPLEMENTARY WELL HISTORY
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  June 30  Vell No. 5 (MD) is located 350 ft. from S line and 30 ft. from W line of sec 3.V./A 3.V./A 3.C. 5 27 H 8 W H.M.F.M.  (K Sec. and Sec. No.) (Twp.) (Range) (Moridian)  Sence M.V. Dakota Wildowt San Juan Rew Mexico (Field)  (County or Bubdivision) (State or Territory)  The elevation of the derrick floor above sea level is 5243 ft.  DETAILS OF WORK  tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding in points, and all other important proposed work)  (State or Territory)  The clevation of the derrick floor above sea level is 5243 ft.  DETAILS OF WORK  tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding in points, and all other important proposed work)  (State or Territory)  The clevation of the derrick floor above sea level is 5243 ft.  DETAILS OF WORK  tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding in points, and all other important proposed work)  (State or Territory)  (St	(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  June 30  No. 5 (ND) is located 350 ft. from S line and 20 ft. from W line of sec.  A S.W./A Sec. 5 27 H S W H.M.P.M.  (Kee, and Sec. No.)  (Kee, and Sec. No.)  (County of Bubdivision)  (County of Bub	(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  June 30  [Vell No. 5 (ND) is located 350 ft. from S line and 320 ft. from W line of sec	E OF REPORT, NOTICE, OR OTHER DATA)
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  Jame 30  Vell No. 5 (ND) is located 350 ft. from S line and ft. from W line of sec 3.V./A S.V./A Sec. 5 27 H S W H.M.P.N.  (K Sec. and Sec. No.) (Twp.) (Range) (Moridian) (State or Territory)  SENCE M.V. Dakotas Wildcat Sen Juan (County or Subdivision) (State or Territory)  The elevation of the derrick floor above sea level is 5243 ft.  DETAILS OF WORK  tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding in points and all other important proposed work)  1 3-3-60. Total Dayth 7035. Rans 39 ths. (669') 7", 23 # 8-60 casing. 3038') 7" 23 # 8-60 casing. 3038' 7 Plug/six., 0.04 # HR-h & 50 size. Heat. Two stage collars & 4957'. Cascond stage w/230 size. 50-50 Diamix, 4 # Gal, 1 # Plocele/sk, 1 ft Plug/six., 0.04 # HR-h & 50 size. Heat. Two stage collars & 4957'. Cascond stage w/230 size. 50-50 Diamix, 2 # Gal, 2 # calcium chloride 2.  Second stage - \$350'  Second stage - \$183'  Third stage - \$150	(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  June 30  No. 5 (ND) is located 350 ft. from S line and 20 ft. from W line of sec.  A S.W. /A Sec. 5 27 S S S S.M. P.M.  (Of Sec. and Sec. No.)  (Of Sec. and Sec. No.)  (County or Subdivision)  (County or Subdivision)  (State or Territory)  (State or Territory)  (County or Subdivision)  (State or Territory)  (County or Subdivision)  (State or Territory)  (State or Territory)  (State or Territory)  (DETAILS OF WORK  (State or Territory)  (State or Territ	(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  June 30  , 19  /ell No. 5 (ND) is located 350 ft. from S line and ft. from W line of sec.  I.V./A S.V./A S.C. 5 27 N S W R.M.P.N.  (V. Soc. and Sec. No.) (Typ.) (Range) (Moridian) (Range) (Moridian) (State or Territory)  Among M.V. Delkotts Wildest San Juan (Moridian) (State or Territory)  he elevation of the derrick floor above sea level is 50 ft.  DETAILS OF WORK  Late names of and expected depths to objective sands; and all other important proposed work)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts. (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts. (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (569°) 7", 23 ft N-80 cassing. 160 fts. (1900)  1-3-50. Total Depth 7035. Ran 39 fts. (190	E OF REPORT, NOTICE, OR OTHER DATA)
Vell No. 5 (ND) is located 550 ft. from S line and ft. from W line of second stage w/230 sim. 50-50 Diamix, 2 f Gel, 2 calcium chloride 2.  San June 30  The second stage - 1350  Lunderstand that this plan of work must receive approval in writing by the Geological Survey before the second stage - 1350  Lunderstand that this plan of work must receive approval in writing by the Geological Survey before the second stage - 1350  Lunderstand that this plan of work must receive approval in writing by the Geological Survey before the second stage - 1350  Lunderstand that this plan of work must receive approval in writing by the Geological Survey before the second stage - 1350  Lunderstand that this plan of work must receive approval in writing by the Geological Survey before the second stage - 1350  Lunderstand that this plan of work must receive approval in writing by the Geological Survey before the second stage - 1350  Lunderstand that this plan of work must receive approval in writing by the Geological Survey before the second stage - 1350  Lunderstand that this plan of work must receive approval in writing by the Geological Survey before the second stage - 1350  Lunderstand that this plan of work must receive approval in writing by the Geological Survey before the second stage - 1350  Lunderstand that this plan of work must receive approval in writing by the Geological Survey before the second stage - 1350	No. 5 (ND) is located 350 ft. from S line and 20 ft. from W line of sec.  A 8.W./4 Sec. 5 27 S 8 W S.M.P.N.  (K Sec and Sec. No.) (Twp) (Range) (Meridian)  Co M.V. Dakota Wildout San Jazan Rew Merrico  (Field) (County or Subdivision) (State or Territory)  elevation of the derrick floor above sea level is 6243 ft.  DETAILS OF WORK  names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding jobs, cames of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding jobs, cames 3-60. Total Dayth 7035. Ram 39 its. (669') 7", 23 S-80 casing. 160 jts.  3-60. Total Dayth 7035. Ram 39 its. (669') 7", 23 S-80 casing. 160 jts.  3-7 23 3, 3-55 casing. 25 jts. (259') 7" 23 S-80 casing. Total 224 jts.) set at 7026.  stage consented w/100 sks. 50-50 Diamin, 4 Gel, 1 Plocele/sk, 1 Fine Ping/sk., 0.04 SR-4 50 sks. Rest. Two stage collars 8 4957'. Committed a stage w/230 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third stage w/100 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third stage w/100 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third stage w/100 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third stage w/100 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third stage w/100 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third stage w/100 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third stage w/100 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third stage w/100 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third stage w/100 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third stage w/100 sks. 50-50 Diamin, 2 Gel, 2 Staleium chloride 2. Third collars 2537'. Committed third st	/ell No. 5 (ND) is located 350 ft. from S line and 320 ft. from W line of sec.  1.W./A S.W./A Sec. 5 27 H S W H.M.P.N.  (A Sec. and Sec. No.)  (B Sec. and Sec. And Sec. Sec. No.  (B Sec. and Sec. No.)  (B Sec. and Sec. And Sec. Sec. No.  (B Sec. and Sec. Sec. No.  (B Sec. and Sec. Sec. Sec. Sec. Sec. Sec. Sec. Sec.	
Vell No. 5 (ND) is located 350 ft. from S line and 1. V./A S.V./A Sec. 5 27 H S W H.M.F.N.  (C) Sec. and Sec. No.)  (C) Sec. and Sec. No.  (C) Sec. and S	No. 5 (ND) is located 350 ft. from S line and ft. from W line of sec.  A S.W./A Sec. 5 27 H S W H.M.P.N.  (K Sec. and Sec. No.) (Twp.) (Range) (Meridian)  CO M.V. Dalkota Wildcat San Juan (State or Territory)  clevation of the derrick floor above sea level is 5243 ft.  DETAILS OF WORK  DETAILS	/ell No. 5 (ND) is located 350 ft. from S line and ft. from W line of sec	June 30
W. A. S. W. A. Sec. 5 27 H & W H. P. N.  (C) Sec. and Sec. No.)  (C) Sec. and Sec. No.)  (C) County or Subdivision)  (State or Territory)  (State or Territory)  (State or Territory)  (C) County or Subdivision)  (C) County or Subdivision)  (C) County or Subdivision)  (State or Territory)  (	(No. 27 May 1997)  (State or Territory)  (State or Territory)	Of Sec. and Sec. No.)  Of Sec. Market San Juan  Of Sec. Sec. Sec. Sec. Sec. Sec. Sec. Sec.	10
W. A. S. W. A. Sec. 5 27 H & W H. P. N.  (C) Sec. and Sec. No.)  (C) Sec. and Sec. No.)  (C) County or Subdivision)  (State or Territory)  (State or Territory)  (State or Territory)  (C) County or Subdivision)  (C) County or Subdivision)  (C) County or Subdivision)  (State or Territory)  (	(Note and Sec. No.)  (Note and Sec. No.)  (Pield)  (County or Subdivision)  (State or Territory)  (State or Te	Of Sec. and Sec. No.)  Of Sec. Market San Juan  Of Sec. Sec. Sec. Sec. Sec. Sec. Sec. Sec.	, 17.
(% Sec. and Sec. 5)  (% Sec. and Sec. 5)  (Twp.)  (Range)  (Meridian)  (Residence M.V. Dakkoth Wildort  San Jaan  (County or Subdivision)  (State or Territory)  The elevation of the derrick floor above sea level is  (County or Subdivision)  (State or Territory)  The elevation of the derrick floor above sea level is  (County or Subdivision)  (State or Territory)  (State or	(No. 1960. and Sec. No.)  (No. 1960. and Sec. No.)  (No. 1960. No.)  (No. 1960. and Sec. No.)  (Picid)  (County or Subdivision)  (State or Territory)  (St	Of Sec. and Sec. No.)  Of Sec. and Sec. No.  Of Sec. and Sec. No.)  Of Sec. and Sec. No.  Of Sec. and Se	line and ft. from W line of sec
Rev Mexico  (Field)  (County or Subdivision)  (State or Territory)  The elevation of the derrick floor above sea level is the state of proposed casings; indicate mudding in points, and all other important proposed work)  (County or Subdivision)  (State or Territory)  DETAILS OF WORK  At a names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding in points, and all other important proposed work)  (County or Subdivision)  DETAILS OF WORK  At a names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding in points, and all other important proposed work)  (County or Subdivision)  (State or Territory)	CO M.V. Dekota Wildowt San Juan (County or Subdivision)  County or Subdivision  County or Subdivision)  County or Subdivision  Cou	me co M.V. Dakota Wildost San Jaan Rev Mexico  (Picki) (County or Subdivision) (State or Territory)  the elevation of the derrick floor above sea level is 5243 ft.  DETAILS OF WORK  ate names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding jobs, ceme ing points, and all other important proposed work)  3-3-60. Total Depth 7035. Rem 39 jts. (669') 7", 23 % N-80 casing. 160 jts.  383') 7 " 23 %, J-55 casing. 25 jts. (258') 7" 23 % N-80 casing. Total 224 jts.  355') 8 set at 7028.  367 Plug/sc., 0.04 % RR-4 & 50 sks. Heat. Two stage collar 8 4957'. Commute stage w/230 sks. 50-50 Diamix, 2 % Gel., 2 % calcium chloride 2. Third allows chloride 2.  350' Second stage - 183'  31 Paso Satural Ges Company  ORIGINAL SIGNED H.E. McANALLY  Ferminaton. Here Mexico.  ORIGINAL SIGNED H.E. McANALLY	
(Field) (County or Subdivision) (State or Territory)  The elevation of the derrick floor above sea level is 5243 ft.  DETAILS OF WORK  At a names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding in property of the proposed depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding in property of the proposed depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding in property of the proposed depths to object in property of the proposed depths to object in property of the proposed depths of the	clevation of the derrick floor above sea level is  DETAILS OF WORK  names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemering points, and all other important proposed work)  3-60. Total Depth 7035. Ram 39 jts. (669') 7", 23 # 8-60 casing. 160 jt.  3') 7 " 23 #,J-55 casing. 25 jts. (258') 7" 23 # 8-60 casing. Total 224 jt.  3 set at 7026.  3 stage cemented w/100 sks. 50-50 Diamin, 4 5 Gel, 4 Plocele/sk, 4 Fin Plug/sks., 0.04 # 88-4 5 50 sks. Heat. Two stage collar 8 4957'. Camented & stage w/230 sks. 50-50 Diamin, 2 # Gel, 2 % calcium chloride 2. Third collar 2567'. Camented third stage w/100 sks. 50-50 Diamin, 2 # Gel, 2 % calcium chloride 2.  At Tops:  First stage - 350' Second stage - 1950  deretand that this plan of work must receive approval in writing by the Geological Survey before dealth may be companied any.  Brow (27)	(Pield) (County or Subdivision) (State or Territory)  ne elevation of the derrick floor above sea level is 5243 ft.  DETAILS OF WORK  ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cems ing points, and all other important proposed work)  3-3-60. Total Depth 7035. Rem 39 jts. (669') 7", 23 % 8-80 casing. 160 jts. (258') 7" 23 % 3-80 casing. 160 jts. (258') 7" 23 % 8-80 casing. Total 224 jts. (258') 7" 23 % 8-80 casing. Total 224 jts. (258') 7" 23 % 8-80 casing. Total 224 jts. (258') 7" 23 % 8-80 casing. Total 224 jts. (258') 7" 23 % 8-80 casing. Total 224 jts. (258') 7" 23 % 8-80 casing. Total 224 jts. (258') 7" 23 % 8-80 casing. 160 jts. (258') jts. (258') 7" 23 % 8-80 casing. 160 jts. (258') jts. (258') 7" 23 % 8-80 casing. 160 jts. (258') jts. (258') 7" 23 % 8-80 casing. 160 jts. (258') jts. (258') 7" 23 % 8-80 casing. 160 jts. (258') jts. (258') 7" 23 % 8-80 casing. 160 jts. (258') jts. (258') 7" 23 % 8-80 casing. 160 jts. (258') jts. (258') 7" 23 % 8-80 casing. 160 jts. (258') jts. (258') 7" 23 % 8-80 casing. 160 jts. (258') jts. (258') jts. (258') 7" 23 % 8-80 casing. 160 jts. (258') jt	· · · · · · · · · · · · · · · · · · ·
DETAILS OF WORK  ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding in points, and all other important proposed work)  3-3-60. Total Depth 7035. Run 39 jts. (669') 7", 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7", 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-60. Total Depth 7035. Run 39 jts. (669') 7" 23 # 8-80 casing. 3  3-60. Casing at 7026.  3-7-7-7-7-7-7-7-7-7-7-7-7-7-7-7-7-7-7-	DETAILS OF WORK  DETAILS OF WORK  names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, come ing points, and all other important proposed work)  3-60. Total Dayth 7035. Ram 39 its. (669') 7", 23 # 8-60 casing. 160 jt.  3') 7" 23 # 3-55 casing. 25 jts. (258') 7" 23 # 8-60 casing. Total 224 jt.  3) set at 7026.  3 stage camented v/103 sks. 50-50 Diamin, 4 f Gal, 4 Plocele/sk, 4 f Fin Plug/sk., 0.04 # 18-4 & 50 sks. Heat. Two stage collers & 4957'. Camented & stage v/230 sks. 50-50 Diamin, 2 # Gal, 2 * calcium chloride 2. Third coller @ 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 * Gal, 2 * calcium chloride 2.  A Tope:  Pirst stage - 3350' Second stage - 1183' Third stage - 1950  decented that this plan of work must receive approval in writing by the Geological Survey before a Chloride content.  Brue (20)	DETAILS OF WORK  ate names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding jobs, come ing points, and all other important proposed work)  3-3-60. Total Depth 7035. Rem 39 its. (669') 7", 23 # 8-60 casing. 160 its cases of a result of the case of the ca	
23 %,3-55 casing. 25 jts. (258') 7" 23 % N-60 casing. Total 2015) set at 7026.  The stage commented v/100 sks. 50-50 Diamix, 4 % Gel, 1 % Plocele/sk, 1 fing/sk., 0.04 % ER-4 & 50 sks. Heat. Two stage collar 8 4957'. Casend stage v/230 sks. 50-50 Diamix, 2 % Gel, 2 % calcium chloride 2.  The collar 2587'. Commented third stage v/100 sks. 50-50 Diamix, 2 % calcium chloride 2.  The stage - 350'  Second stage - 4183'  Third stage - 1950  Understand that this plan of work must receive approval in writing by the Geological Survey before a CON. Collar of the coll	set at 7020.  Stage camented v/100 sks. 50-50 Diamin, 4 % Gel, 1 Plocele/sk, 1 Fin Plug/sk., 0.04 % HR-4 & 50 sks. Heat. Two stage collar 8 4957'. Committed stage v/230 sks. 50-50 Diamin, 2 % Gel, 2 % calcium chloride 2. Third collar 8 2507'. Committed third stage v/100 sks. 50-50 Diamin, 2 % Gel, 2 % calcium chloride 2. Third cium chloride 2.  Trops:  Piret stage - 350' Second stage - 4183' Third stage - 1950  derstand that this plan of work must receive approval in writing by the Geological Survey before a Climary becomes any DIST.	23 %,3-55 casing. 25 jts. (258) 7 23 % 8-80 casing. Total 224 jt  15) set at 7028.  Total tage camented v/100 sks. 50-50 Diamin, 4 5 Gel, 2 Plocele/sk, 1 Fin  17 Plug/sk., 0.04 % ER-4 & 50 sks. Hest. Two stage collar 8 4957'. Camente  180 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  181 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  182 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  182 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  183 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  184 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  185 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Gel,  185 collar 8 2587'. Camented third stage v/100 sks. 50-50 Diami	
ret stago camented v/100 sks. 50-50 Diamin, 4 5 Gal, 1 7 Plocele/sk, 1 ff Plug/sk., 0.04 5 ER-4 5 50 sks. Heat. Two stage collar 6 4957'. Ca cond stage v/230 sks. 50-50 Diamin, 2 5 Gal, 2 5 calcium chloride 2. age collar 6 2507'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 calcium chloride 2. ment Tops:  First stage - 6350' Second stage - 4183' Third stage - 1950  I understand that this plan of work must receive approval in writing by the Geological Survey before a CON. Co. DIST. 3	stage commented v/100 sks. 50-50 Dismin, 4 5 Gel, 1 Plocele/sk, 1 f Fin Plug/sk., 0.04 5 HR-4 & 50 sks. Heat. Two stage collar 6 4957'. Committee at stage v/230 sks. 50-50 Dismin, 2 5 Gel, 2 5 calcium chloride 2. Third collar 6 2507'. Commented third stage v/100 sks. 50-50 Dismin, 2 5 Gel, 2 5 calcium chloride 2. It tops:  Pirst stage - 6350' Second stage - 4183' Third stage - 1950  derstand that this plan of work must receive approval in writing by the Geological Survey before a Climater Construction.  21 Paso Matural Gas Company	ret stage camented v/100 sks. 50-50 Diamix, 4 5 Gel, 2 7 Plocele/sk, 1 7 Fin ff Flug/sk., C.O4 7 ER-4 5 50 sks. Heat. Two stage collar 8 4957'. Committee cond stage v/230 sks. 50-50 Diamix, 2 7 Gel, 2 7 calcium chloride 2. Third age collar 8 2507'. Committee third stage v/100 sks. 50-50 Diamix, 2 6 Gel, 2 6 calcium chloride 2. Third stage - 3350'. Second stage - 5350'. Second stage - 5350'. Second stage - 5350'. Third stage - 5350'. Independent of the following stage - 5350'. Third stage - 5350'. Third stage - 5350'. Second stage - 5350'. Second stage - 5350'. Third stage - 5350'. Second	(669') 7", 23 # N-80 casing. 160 y
ret stage camented v/100 sks. 50-50 Diamin, 4 5 Gel, 2 Plocele/sk, 1 If Plug/sk., 0.04 5 HR-4 5 50 sks. Heat. Two stage collar 8 4957'. Co cond stage v/230 sks. 50-50 Diamin, 2 5 Gel, 2 5 calcium chloride 2. age collar 8 2587'. Comented third stage v/100 sks. 50-50 Diamin, 2 5 calcium chloride 2. sent Tope:  Pirst stage - 6350' Second stage - 4183' Third stage - 1350  I understand that this plan of work must receive approval in writing by the Geological Survey before CON. Co.  Til Pago Battural Gam Commons.	Stage committed v/100 sks. 50-50 Diamin, 4 5 Gel, 2 Plocele/sk, 1 Find Plug/sk., 0.04 5 HR-4 & 50 sks. Hest. Two stage collar 8 4957'. Committed stage v/230 sks. 50-50 Diamin, 2 5 Gel, 2 5 calcium chloride 2. Third collar 8 2587'. Committed third stage v/100 sks. 50-50 Diamin, 2 5 Gel, 2 5 calcium chloride 2. It Tope:  Pirst stage - 6350' Second stage - 4183' Third stage - 1950  derstand that this plan of work must receive approval in writing by the Geological Survey before a Clim May be commenced.  Ill Paso Natural Gas Company  Boar (63)	ret stage camented v/100 sks. 50-50 Diamin, 4 5 Cal, 1 7 Placele/sk, 1 7 Fin ff Flug/sk., C.O. 5 BR-4 5 50 sks. Heat. Two stage collar 8 457'. Camente cond stage v/230 sks. 50-50 Diamin, 2 5 Cal, 2 5 calcium chloride 2. Third age collar 2 2507'. Camented third stage v/100 sks. 50-50 Diamin, 2 5 Cal, calcium chloride 2.  Pirst stage - 350' Second stage - 4183' Third stage - 1350  I understand that this plan of work must receive approval in writing by the Geological Survey before COM.  The Paso Natural Cas Company  ORIGINAL SIGNED H.E. McANALLY  ORIGINAL SIGNED H.E. McANALLY	)') 7" 23 # 8-80 casing. Total 224 3
IX Fine/Sz., 0.04 % ER-4 & 50 sks. Heat. Two stage coller 8 4957'. Cocond stage v/230 sks. 50-50 Diamix, 2 % Gel, 2 % calcium chloride 2.  age coller 8 2587'. Comented third stage v/100 sks. 50-50 Diamix, 2 % calcium chloride 2.  Best Tops:  First stage - 350' Second stage - 4183' Third stage - 1950  I understand that this plan of work must receive approval in writing by the Geological Survey before CON. CON. CON. CON. CON. CON. CON. CON.	A stage v/230 sks. 50-50 Diamix, 2 % Gel, 2 % calcium chloride 2. Third coller @ 2507'. Comented third stage v/100 sks. 50-50 Diamix, 2 % Gel, 2 % calcium chloride 2. Third clum chloride 2.  Third stage - 6350'  Second stage - 5183'  Third stage - 1950  derstand that this plan of work must receive approval in writing by the Geological Survey before a Clim CON. CON.  The Paso Natural Gas Company  Rese (33)	Cond stage v/230 siz. 50-50 Diamin, 2 i Gel, 2 calcium chloride 2. Third age collar @ 2507'. Comented third stage v/100 size. 50-50 Diamin, 2 Gel, 2 calcium chloride 2. Third calcium chloride 2.  Second stage - 6350'  Second stage - 6350'  Second stage - 6350'  I understand that this plan of work must receive approval in writing by the Geological Survey before Collar of the Control of the Cont	dr. h & day & & Planetales 1 & ve
Some stage v/2/0 Sis. 50-50 Diamix, 2 % Gel, 2 % calcium chloride 2.  Age collar @ 2507'. Comested third stage v/100 sks. 50-50 Diamix, 2 % calcium chloride 2.  Bent Tope:  First stage - 6350' Second stage - 4183' Third stage - 1950  [ULL 6 196]  [Ull 6 196]  [Ull 6 196]  [Ull 6 196]  [Ull 7 8 196]  [Ull 6 196]  [Ull 6 196]  [Ull 7 8 196]  [Ull 8 196]  [Ull 7 8 196]  [Ull	destand that this plan of work must receive approval in writing by the Geological Survey before a CON. COM.  The Paso Natural Gas Company  Boar (87)	Second stage - 350'  Second stage - 1350'  I understand that this plan of work must receive approval in writing by the Geological Survey before CON. COM.  The Paso Natural Cas Company  ORIGINAL SIGNED H.E. McANALLY  Fermination. New Mexico.	Two stame coller & 40571 Comments
Second stage - 6350'  Second stage - 4183'  Third stage - 1350  I understand that this plan of work must receive approval in writing by the Geological Survey before CON. CON. CON. CON. CON. CON. CON. CON.	counter 2507. Comested third stage v/100 shs. 50-50 Diamix, 2.5 Gel, cium chloride 2.  It Tope:  Pirst stage - 3350' Second stage - 1183' Third stage - 1950  derstand that this plan of work must receive approval in writing by the Geological Survey before of the may be commenced.  The Paso Natural Gas Company  Brow (37)	Piret stage - 350' Second stage - 1950  I understand that this plan of work must receive approval in writing by the Geological Survey before and the many many Box 990  DIST. Signed H.E. McANALLY  ORIGINAL SIGNED H.E. McANALLY	Gal. 2 % ealetim chlowide 9. Whim
First stage - 6350' Second stage - 4183' Third stage - 1350  I understand that this plan of work must receive approval in writing by the Geological Survey before a CON. CON. CON. CON. CON. CON. CON. CON.	Pirst stage - 6350' Second stage - 8183' Third stage - 1950  derstand that this plan of work must receive approval in writing by the Geological Survey before a CON. COM.  The Paso Satural Gas Company  Brow (63)	Pirst stage - 350' Second stage - 123' Third stage - 1250  I understand that this plan of work must receive approval in writing by the Geological Survey before CON. COM.  The Paso Natural Cas Company  DIST. Signed H.E. McANALLY  Perministra. New Marries  ORIGINAL SIGNED H.E. McANALLY	p v/100 sks. 50-50 Diemix, 2 € Gel,
First stage - 6350' Second stage - 4183' Third stage - 1950  [ understand that this plan of work must receive approval in writing by the Geological Survey before collaboration of the CON. CON. CON. CON. CON. CON. CON. CON.	First stage - 330' Second stage - 123' Third stage - 1250  derstand that this plan of work must receive approval in writing by the Geological Survey before of the may be commenced.  The Paso Matural Gas Company  Brow (33)	First stage - 350' Second stage - 1350  I understand that this plan of work must receive approval in writing by the Geological Survey before a Collection of the Congression of the Cong	Continue of the second
Second Stage - 4183' Third stage - 1950  Jul 6 196  I understand that this plan of work must receive approval in writing by the Geological Survey before of CON. Comments and Construction of	Second stage - 133' Third stage - 1350  derstand that this plan of work must receive approval in writing by the Geological Survey before a CIL may be commenced.  21 Page Matural Gas Company  Brow (33)	Second stage - 1931  Third stage - 1950  I understand that this plan of work must receive approval in writing by the Geological Survey before a CON. COM.  The Paso Natural Cas Company  In Paso Natural Cas Company  ORIGINAL SIGNED H.E. McANALLY	OHLTIVE
I understand that this plan of work must receive approval in writing by the Geological Survey before of the may be compared to the Control of	derstand that this plan of work must receive approval in writing by the Geological Survey before of GIL. May be commenced.  22 Page Satural Gas Company  Brow (33)	I understand that this plan of work must receive approval in writing by the Geological Survey before CON. COM.  The Paso Satural Cas Company  Box 900  ORIGINAL SIGNED H.E. McANALLY	/ Wroc,
	any Row (AT)	Idress ORIGINAL SIGNED H.E. McANALLY	su 6 1960
	any Row (NY)	dress ORIGINAL SIGNED H.E. McANALLY	JULO COM
AL PERO BELLEVI GRA COMMENT	any Row (AT)	dress ORIGINAL SIGNED H.E. McANALLY	by the Geological Survey before de Gibes may be commenced.
	Box 930	Perminsten Novince ORIGINAL SIGNED H.E. McANALLY	Digira
dress	aa	Formation November ORIGINAL SIGNED H.E. McANALLY	
	ODICINAL COMED HE MANALIV		
Company	Rose (SY)	Idress ORIGINAL SIGNED H.E. McANALL	FILLY 1. 1960  JUL 6 1960  The Goological Survey before a COM. COM. DIST. 300 percent.
ompany Il Paso Matural Gas Company	Row (XY)	Idress Box 90	