MULTIPLE COMPLETE CHANGE ZONES

ABANDON\*

(other)

REQUEST FOR APPROVAL TO:

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Dec. 1973	budget bureau No. 42-81424	
UNITED STATES  DEPARTMENT OF THE INTERIOR	5. LEASE SF-078481-A	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME  8. FARM OR LEASE NAME	
1. oil gas other	Graham - 9. WELL NO.	
2. NAME OF OPERATOR R & G DRILLING COMPANY  3. ADDRESS OF OPERATOR c/o Walsh Engr. & Prod. Corp	33  10. FIELD OR WILDCAT NAME Blanco PC South  11. SEC., T., R., M., OR BLK, AND SURVEY OF AREA Sec. 4-T27N-R8W N.M.P.M.	
2.0. Drawer 419, Farmington, NM. 87499  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)		
AT SURFACE: 980'FNL, 800'FEL AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same	12. COUNTY OR PARISH 13. STATE San Juan N.M.  14. AP! NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5897 GL	

change on Form 9-330.)

TEST WATER SHUT-OFF FRACTURE TREAT RECEIVED SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone PULL OR ALTER CASING

BUREAU OF LAND MANAGEMENT

**FARMINGTON RESOURCE AREA** 

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12/4/85 Well plugged and abandoned in the following manner:

SUBSEQUENT REPORT OF:

- Set 79 cu. ft. (67 sacks) cement plug from 1600' to 2186'.
- Set 14 cu. ft. (12 sacks) cement plug from 1080' to 1180'. 2.
- Bradenhead squeeze with 59 cu. ft. (50 sacks) leaving 50 feet cement across 8-5/8" surface casing shoe.
- Squeeze down 5-1/2" casing with 89 cu. ft. (75 sacks).
- Set 12 cu. ft. (10 sacks) in top of 5-1/2" casing with dry 5. hole marker.

Subsurface Safety Val	ve: Manu. and Type	Set @	Ft.
FOR: R 18. I hereby certify th	& G DRILLING COMPANY <b>ORIGHNALES (CAUE</b> true and correst resident, Walsh		
SIGNED	Walsh, P.E. TITLE Engr. & Prod. DA	12/13/85	<u>్ట</u>
Ewell N.	(This space for Federal or State office use)		
		DATE	
CONDITIONS OF APPRO	VAL. IF ANY:	<u>.</u>	

eer as to plut 14 d ee My under bons to 10 cade restoration is completed.

\*See Instructions on Reverse Side