Form 9-381a RLUL MAY 1 2 I	CDEPARTMENT OF THE	ATES HE INTERIOR Losse No. 079052 Unit Rincon Unit
SUNDRY NOTICE OF INTENTION TO DRILL	SUBSEQU	EPORTS ON WELLS QUENT REPORT OF WATER SHUT-OFF RECEIVED
NOTICE OF INTENTION TO CHANGE PL NOTICE OF INTENTION TO RE-DRILL O NOTICE OF INTENTION TO SHOOT OR NOTICE OF INTENTION TO PULL OR AI	R SHUT-OFF SUBSEQUENCE SUBSEQU	QUENT REPORT OF SHOOTING OR ACIDIZING AY 9 1935 QUENT REPORT OF ALTERING CASING COULD COLOR QUENT REPORT OF RE-DRILLING OR REPUR NOTON, HEW MEX
NOTICE OF INTENTION TO ABANDON V		ster Frec. X
Well No. 306 is located is located to the second sec. 18	ed 800 ft. from \bigg\{\bigg\} \bigg\} line	e and 1683 ft. from E line of sec. 18 N.N. P.N. (Meridian)
So. Blanco P.C. Bet. (Field)	Rio Arrisa (County or Subdivision)	New Nexteo
	DETAILS OF Woodpective sands; show sizes, weights, and all other important	WORK and lengths of proposed casings; indicate mudding jobs, cement-
perforated intervals send. B.D.P. 18504.	3184-3198; 3204-3220 v	". Water fractured Pictured Cliffs with 35,102 gallons water and 35,000# tr. pr. 1800-2000-2300-2200#. I.R. sets of 10 balls for 3 stages.
perforated intervals send. B.D.P. 18704, 41 B.P.H. Flush 328	3184-3196; 3204-3220 w max. pr. 2300%, avg. t	with 35,102 gallons water and 35,000# tr. pr. 1800-2000-2300-2200#. I.R.

Petroleum Engineer

GPO 918507

Title ____