OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	CONOCO INC		Lease	SAN JUAN 2	8-7 UNI	Well L No.	93 (PM)	
Location of Well: Unit <u>N</u>	Sec0.9	Twp. <u>27</u>	Rge	07	Cour	nty <u>RI</u>	O ARRIBA	
	NAME OF RESERVOIR OR POOL			[METHOD OF PROD. (Flow or Art. Lift)		PROD. MEDIUM (Tbg. or Cag.)	
Upper Completion PICTURED CLIFF Lower Completion MESA VERDE			GAS	F	FLOW		TBG.	
			GAS	F			TBG.	
		PRE-FLO	W SHUT-IN P	RESSURE DATA				
Upper Hour, date shut-in 0.4.16.95 Lower Hour, date shut-in		3-DAYS			Si press. paig 137 Si press. paig		Stabilized? (Yes or No) NO Stabilized? (Yes or No)	
Completion 04-	16-95	3-DAYS	170			NO		
			FLOW TEST	NO. 1				
Commenced at (hour, da	te)# 04-15			Zone producing (Up	per or Lowerk L	OWER		
TIME (hour, date)	LAPSED TIME SINCE*		PRESSURE Upper Completion Lower Completion		REMARKS			
04-17-94	1-Day	123	160	TEMP.	BOTH ZONES SHUT -IN			
04-18-95	2-Days	135	170		BOTH ZONES SHUT -IN			
04-19-95	3-Days	137	170		BOTH ZONES SHUT -IN			
04-20-95	1-Day	140	118		LOWER ZONE FLOWING			
04-21-95	2-Days	140	125		LOWER ZONE FLOWING			
	•	D based on				G12v	GOR	
Gas:				(Orifice or Mete	r):			
Hour date	thutin	MID-1ES		RESSURE DATA		Stabilized?	(Yes or No)	
Upper Completion					SI press, paig		Stabilized? (Yes or No)	
Lower Completion	f .		Length of time shut-in			Prenditage () as or wol		
1								

(Continue on reverse side)

FLOW TEST NO. 2

ommenced at (hour, o	V=14/7 T		Zone producing (Upper or Lower):			
TIME	LAPSED TIME	PRESSURE		PROD. ZONE		
(hour, dete)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS	
]			
						
oduction rate			1			
					Grav GOR	
us:		MCFI	PD: Tested thru	(Orifice or Meter):		
				<u> </u>		
	- 					
nereby certify t	hat the informatio	on herein containe	ed is true and cor	nplete to the best	of my knowledge.	
	Johnny Role			perator		
New Mexico 🛭	il Conservation D	ivision	/	perator		
	JUN 1 4 19	005	В	,		
	0011 1 1	,33	·	DDAN	CTION SPECIALIS	
	_		Ti	of UODO	ULIUN OF LUIALIO	
	TEDUTY OF CACIA					
ie	DEPUTY OIL & GAS IN	ISPECTOR		ateC	UNIOCO INC	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever temedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5 Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).