

X			

Land Office Santa Fe

Lease No. 0710-2

Unit San Juan 28-7
34-09-001-449

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 15 1950

Well No. 106-X (PM) is located 100 ft. from NE line and 1150 ft. from NE line of sec. 10

SW 1/4 of Sec. 10
(1/4 Sec. and Sec. No.)

T2N
(Twp.)

7W
(Range)

104E
(Meridian)

Se. Blanca P.C. & Blanca M.V. Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 662 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding logs, cementing points, and all other important proposed work)

On August 30, 1950, Total Depth 5664'.

Ran 56 joints 5 1/2", J-55, 15.50# liner (2299') set from 3350' to 5650' with 160 sacks regular cement, 160 sacks Diamix, 1/4".

Floccle/sk, 1/2# Fine Tuf Plug/sk, and 6% Gel, followed with 50 sacks regular cement. Set Baker Bullbore cementer at 3240'. Squeezed top of liner with 100 sacks regular cement. Maximum and final squeeze pressure - 2000 psi.

Hold 1000-30 minutes.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 27

-----**Elmington, New Mexico**-----

ORIGINAL SIGNED H.E. McANALLY
By _____

Title ~~Petroleum Engineer~~

