i			
İ			
1	1		
		j	
ı	i	!	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

		iu No. 42- ires 12-31-	
Land Office	saate	. Fe	
Lease No.	J7\50	>ラ	
Unit A	Juan	26-7	Unit
14-0	ارتن - 🗓	-459	

NOTICE OF INTENTION TO DRILL	
I NOTICE OF INTENTION TO DIVIET	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
	NATURE OF REPORT, NOTICE, OR OTHER DATA)
(INDICATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR OTHER DATA/
	January 21 , 1957
Well No. is located 1000 ft. from	$\left\{\begin{array}{c} N \\ S \end{array}\right\}$ line and $\left\{\begin{array}{c} 1840 \\ W \end{array}\right\}$ ft. from $\left\{\begin{array}{c} 1840 \\ W \end{array}\right\}$ line of sec. $\left\{\begin{array}{c} 1840 \\ W \end{array}\right\}$
(½ Sc. and Sec. No.) (Twp.)	(Range) (Meridian)
(Field) (County of	or Subdivision) (State or Territory)
The elevation of the derrick floor above sea lev	vel is 55% ft.
State names of and expected depths to objective sands; show siz ing points, and all c	es, weights, and lengths of proposed casings; indicate mudding jobs, cemen ther important proposed work)
12-15-50, Total Depth 3430'.	
Ren 110 joints 5 1/2", 15.50%, J-55	casing (3420') set at 3430' with 50 secks Gel, fullowed by 50 secks regular cessent. at 2000'. RELITY 10 OR CON COM. DIST 2
Ran 110 joints 5 1/2", 15.50%, J-55 regular cement, 50 sacks Pozzaix, 4% Seld 1000% for 30 minutes. Top of cement by temps rature survey	at 2000'. RELIVED ON COM.
Ren 110 joints 5 1/2, 15.50%, J-55 regular cement, 50 sacks Poznik, 15 Seld 1000% for 30 minutes. Top of cement by temps rature survey	at 2000. Oil CON COM DIST. 2 writing by the Geological Survey before operations may be commenced.
Ran 110 joints 5 1/2", 15.50%, J-55 regular cement, 50 sacks Pozzaix, 4% Seld 1000% for 30 minutes. Top of cement by temps rature survey	st 2000'. OIL CON COM. DIST. 2 writing by the Geological Survey before operations may be commenced.
Ren 110 joints 5 1/2, 15.50%, J-55 regular cement, 50 sacks Pozzaix, 4% Seld 1000% for 30 minutes. Top of cement by temps rature survey [understand that this plan of work must receive approval in Company 21 Paso 4 turni Cas Company	at 2000. Oil CON COM DIST. 2 writing by the Geological Survey before operations may be commenced.

U.S. GOVERNMENT PRINTING OFFICE: 1956--O-393560

