

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company Attn: John Hampton

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1800' FNL, 1840' FWL, Sec. 8, T27N-R7W

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.  
Sf-078565

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

San Juan 28-7 Unit 66

9. API Well No.

30 039 07128

10. Field and Pool, or Exploratory Area

S. Blanco Pictured Cliffs

11. County or Parish, State

Rio Arriba, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Amoco Production Company intends to Plug and Abandon the subject well.  
See Attached for procedure:

**RECEIVED**  
SEP 25 1992  
OIL CON. DIV.  
DIST. 3

If you have any questions please call Julie Acevedo at 303-830-6003.

14. I hereby certify that the foregoing is true and correct

Signed

*John Hampton*

Title Sr. Staff Admin. Supv.

Date

9-15-92

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

SEP 24 1992

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side

NMOCD

PXA Procedures  
San Juan 28-7 #66

1. Check location for anchors. Install if necessary. Test anchors.
  2. MIRUSU. Blow down well Kill if necessary with fresh water.
  3. POOH with 1 1/4" tbg and lay down. TIH with bit and scraper, clean out tubing to PBTD. RIH with 2 3/8" work string and retainer. Set retainer at 3300'. Test casing integrity to 1000#.
  4. Squeeze perfs from 3348' to 3366' with 15 sx class B cement. Pull out of retainer and spot cement plug to 2378' with 157 sx class B cement.
  5. Load hole from 2378' to 200' with 9lbs mud/POZ water.
  6. RIH with perforating gun and shoot squeeze holes @200'.
  7. RIH with tbg and pkr or retainer. Set retainer/pkr above the perfs and attempt to circulate to surface with 59 sx class b cement.
  8. Spot cement plug from 200' to surface with 34 sx class b cement.
  9. NDBOPE. Cut off casing and wellhead. Install PXA marker according to BLM or state requirements.
  10. Turn over to John Schwartz for reclamation.
  11. Rehabilitate location according to BLM or state requirements.
-

SJ 28-7 UNIT 066 1995  
Location - 8F- 27N- 7W  
SINGLE PC  
Orig. Completion - 1/57  
Last File Update - 1/89 by DDM

BOT OF 8.625 IN OD CSA 133  
28.5 LB/FT  
TOC - SURF  
OJO ALAMO @2428-2590  
KIRTLAND @2590-3102  
FRUITLAND @3102-3350

PC--SPF PERF 3348-3366 ]

PBTD AT 3380 FT.

BOT OF 1.25 IN OD TBG AT 3371

TOTAL DEPTH 3430 FT.

15.5 LB/FT  
BOT OF 5.5 IN OD CSA 3430  
TOC - 2080TS

FILENAME:  
03907128

TOC @2080 BY TEMP SURVEY