COPY FOR STATE OF NEW MEXICO OIL CONSERVATION COMMISSION SUBMIT IN TRIPLICATE TO DISTRICT OFFICE

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office	Santa Fe
Lease No	0708 35
Unit	20m11
j.	
<i>!</i>	0 0 4 1001

SUNDRY NOTICE	S AND REPORTS ON WELLS
OTICE OF INTENTION TO DRILL	X SUBSEQUENT REPORT OF WATER SHUT-OFF
OTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
OTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
OTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT.
OTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
OTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
Canco - La Plata (Field) GROUND	Rio Arriba New Mexico (County or Subdivision) (State or Territory)
	sea level is .6776 ft.
ne elevation of the derrick floor above	DETAILS OF WORK
tate names of and expected depths to object indicate muddling jobs, cement it is intended to drill a table pay section with gas circuit	DETAILS OF WORK tive sands; show sizes, weights, and lengths of proposed casings; ting points, and all other important proposed work) well through the Mesa Verde section, drilling lation, and to shoot the Mesa Verde with approx-
tate names of and expected depths to object indicate muddling jobs, cement	DETAILS OF WORK tive sands; show sizes, weights, and lengths of proposed casings; ting points, and all other important proposed work) well through the Mesa Verde section, drilling lation, and to shoot the Mesa Verde with approx-
tate names of and expected depths to object indicate muddling jobs, cement. It is intended to drill at the pay section with gas circuit imately three quarts S.N.G. per Casing program as follows: 9-5/8" - 36 lb. J-55 at	DETAILS OF WORK tive sands; show sizes, weights, and lengths of proposed casings; ting points, and all other important proposed work) well through the Mesa Verde section, drilling lation, and to shoot the Mesa Verde with approx-
tate names of and expected depths to object indicate muddling jobs, cement. It is intended to drill a to the pay section with gas circuit imately three quarts S.N.G. per Casing program as follows: 9-5/8" - 36 lb. J-55 at 6-5/8" - 20 lb. J-55 at W2 Section 6 is 6	DETAILS OF WORK Itive sands; show sizes, weights, and lengths of proposed casings; ting points, and all other important proposed work) well through the Mesa Verde section, drilling lation, and to shoot the Mesa Verde with approx- r foot. 300' with cement to surface.
tate names of and expected depths to object indicate muddling jobs, cement. It is intended to drill a the pay section with gas circular imately three quarts S.N.G. per Casing program as follows: 9-5/8" - 36 lbJ-55 at 6-5/8" - 20 lbJ-55 at 10 lbJ-5	DETAILS OF WORK Stive sands; show sizes, weights, and lengths of proposed casings; ting points, and all other important proposed work) Well through the Mesa Verde section, drilling lation, and to shoot the Mesa Verde with approximation, and to shoot the Mesa Verde with approximation. 300' with cement to surface. 4820' with 300 sacks cement. dedicated to this well. t receive approval in writing by the Geological Survey before
tate names of and expected depths to object indicate muddling jobs, cement. It is intended to drill at the pay section with gas circular imately three quarts S.N.G. per Casing program as follows: 9-5/8" - 36 lb. J-55 at 6-5/8" - 20 lb. J-55 at 10 lb. J-55 at	DETAILS OF WORK Stive sands; show sizes, weights, and lengths of proposed casings; ting points, and all other important proposed work) Well through the Mesa Verde section, drilling lation, and to shoot the Mesa Verde with approximation. 300' with cement to surface. 4820' with 300 sacks cement. dedicated to this well. t receive approval in writing by the Geological Survey before
tate names of and expected depths to object indicate muddling jobs, cement. It is intended to drill a tothe pay section with gas circulated three quarts S.N.G. per casing program as follows: 9-5/8" - 36 lbJ-55 at 6-5/8" - 20 lbJ-55 at 6-5/8"	DETAILS OF WORK Stive sands; show sizes, weights, and lengths of proposed casings; ting points, and all other important proposed work) Well through the Mesa Verde section, drilling lation, and to shoot the Mesa Verde with approximation, and to shoot the Mesa Verde with approximation. 300' with cement to surface. 4820' with 300 sacks cement. dedicated to this well. t receive approval in writing by the Geological Survey before